



Medium Duty Freestanding Jib Crane - 351 Series - From 3000 To 4000 lbs Capacity

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-8-8	3000	8	8	W12X35	6-1/2"	360	1332.0	4040	32320.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-9	3000	8	9	W12X35	6-1/2"	360	1386.0	4040	32320.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-10	3000	8	10	W12X35	6-1/2"	360	1440.0	4040	32320.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-11	3000	8	11	W12X35	6-1/2"	360	1496.0	4040	32320.0	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-12	3000	8	12	W12X35	6-1/2"	360	1550.0	4040	32320.0	13'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-13	3000	8	13	W12X35	6-1/2"	360	1606.0	4040	32320.0	14'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-14	3000	8	14	W12X35	6-1/2"	360	1660.0	4040	32320.0	15'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-15	3000	8	15	W12X35	6-1/2"	360	1716.0	4040	32320.0	16'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-16	3000	8	16	W12X35	6-1/2"	360	1770.0	4040	32320.0	17'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-8-17	3000	8	17	W16X45	7"	360	2507.0	1484	32640.0	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-8-18	3000	8	18	W16X45	7"	360	2570.0	1484	32640.0	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-8-19	3000	8	19	W16X45	7"	360	2632.0	1484	32640.0	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-8-20	3000	8	20	W16X45	7"	360	2695.0	1484	32640.0	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-9-8	3000	9	8	W12X35	6-1/2"	360	1367.0	4565	36517.5	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-9	3000	9	9	W12X35	6-1/2"	360	1421.0	4565	36517.5	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-10	3000	9	10	W12X35	6-1/2"	360	1475.0	4565	36517.5	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-11	3000	9	11	W12X35	6-1/2"	360	1531.0	4565	36517.5	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-12	3000	9	12	W12X35	6-1/2"	360	1585.0	4565	36517.5	13'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-13	3000	9	13	W12X35	6-1/2"	360	1641.0	4565	36517.5	14'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-14	3000	9	14	W12X35	6-1/2"	360	1695.0	4565	36517.5	15'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-9-15	3000	9	15	W12X35	6-1/2"	360	1751.0	4565	36517.5	16'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-16	3000	9	16	W12X35	6-1/2"	360	1805.0	4565	36517.5	17'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-9-17	3000	9	17	W16X45	7"	360	2552.0	1679	36922.5	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-9-18	3000	9	18	W16X45	7"	360	2615.0	1679	36922.5	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-9-19	3000	9	19	W16X45	7"	360	2677.0	1679	36922.5	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-9-20	3000	9	20	W16X45	7"	360	2740.0	1679	36922.5	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-10-8	3000	10	8	W12X35	6-1/2"	360	1402.0	5094	40750.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-9	3000	10	9	W12X35	6-1/2"	360	1456.0	5094	40750.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-10	3000	10	10	W12X35	6-1/2"	360	1510.0	5094	40750.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-11	3000	10	11	W12X35	6-1/2"	360	1566.0	5094	40750.0	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-12	3000	10	12	W12X35	6-1/2"	360	1620.0	5094	40750.0	13'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-13	3000	10	13	W12X35	6-1/2"	360	1676.0	5094	40750.0	14'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-14	3000	10	14	W12X35	6-1/2"	360	1730.0	5094	40750.0	15'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-15	3000	10	15	W12X35	6-1/2"	360	1786.0	5094	40750.0	16'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-16	3000	10	16	W12X35	6-1/2"	360	1840.0	5094	40750.0	17'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-3000-10-17	3000	10	17	W16X45	7"	360	2597.0	1875	41250.0	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-10-18	3000	10	18	W16X45	7"	360	2660.0	1875	41250.0	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-10-19	3000	10	19	W16X45	7"	360	2722.0	1875	41250.0	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-10-20	3000	10	20	W16X45	7"	360	2785.0	1875	41250.0	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-3000-11-8	3000	11	8	W16X45	7"	360	1597.0	5703	45622.5	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-3000-11-9	3000	11	9	W16X45	7"	360	1651.0	5703	45622.5	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-3000-11-10	3000	11	10	W16X45	7"	360	1705.0	5703	45622.5	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-11-11	3000	11	11	W16X45	7"	360	2264.0	2074	45622.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-12	3000	11	12	W16X45	7"	360	2327.0	2074	45622.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-13	3000	11	13	W16X45	7"	360	2392.0	2074	45622.5	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-14	3000	11	14	W16X45	7"	360	2455.0	2074	45622.5	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-15	3000	11	15	W16X45	7"	360	2517.0	2074	45622.5	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-16	3000	11	16	W16X45	7"	360	2580.0	2074	45622.5	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-11-17	3000	11	17	W16X45	7"	360	2974.0	2074	45622.5	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-11-18	3000	11	18	W16X45	7"	360	3045.0	2074	45622.5	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-11-19	3000	11	19	W16X45	7"	360	3114.0	2074	45622.5	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-11-20	3000	11	20	W16X45	7"	360	3185.0	2074	45622.5	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-12-8	3000	12	8	W16X45	7"	360	1642.0	6255	50040.0	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-3000-12-9	3000	12	9	W16X45	7"	360	1696.0	6255	50040.0	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-3000-12-10	3000	12	10	W16X45	7"	360	1750.0	6255	50040.0	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-3000-12-11	3000	12	11	W16X45	7"	360	2309.0	2275	50040.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-12	3000	12	12	W16X45	7"	360	2372.0	2275	50040.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-13	3000	12	13	W16X45	7"	360	2437.0	2275	50040.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-14	3000	12	14	W16X45	7"	360	2500.0	2275	50040.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-15	3000	12	15	W16X45	7"	360	2562.0	2275	50040.0	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-16	3000	12	16	W16X45	7"	360	2625.0	2275	50040.0	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-12-17	3000	12	17	W16X45	7"	360	3019.0	2275	50040.0	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-12-18	3000	12	18	W16X45	7"	360	3090.0	2275	50040.0	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-12-19	3000	12	19	W16X45	7"	360	3159.0	2275	50040.0	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-12-20	3000	12	20	W16X45	7"	360	3230.0	2275	50040.0	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-8	3000	13	8	W16X45	7"	360	2169.0	2478	54502.5	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-9	3000	13	9	W16X45	7"	360	2232.0	2478	54502.5	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-10	3000	13	10	W16X45	7"	360	2295.0	2478	54502.5	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-11	3000	13	11	W16X45	7"	360	2357.0	2478	54502.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-12	3000	13	12	W16X45	7"	360	2420.0	2478	54502.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-13	3000	13	13	W18X55	7-1/2"	360	2647.0	2516	55347.5	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-14	3000	13	14	W18X55	7-1/2"	360	2710.0	2516	55347.5	15'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-13-15	3000	13	15	W16X45	7"	360	2924.0	2478	54502.5	16'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-16	3000	13	16	W16X45	7"	360	2995.0	2478	54502.5	17'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-17	3000	13	17	W18X55	7-1/2"	360	3234.0	2516	55347.5	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-18	3000	13	18	W18X55	7-1/2"	360	3305.0	2516	55347.5	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-19	3000	13	19	W18X55	7-1/2"	360	3374.0	2516	55347.5	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-13-20	3000	13	20	W18X55	7-1/2"	360	3445.0	2516	55347.5	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-14-8	3000	14	8	W16X45	7"	360	2214.0	2683	59010.0	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-9	3000	14	9	W16X45	7"	360	2277.0	2683	59010.0	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-10	3000	14	10	W16X45	7"	360	2340.0	2683	59010.0	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-11	3000	14	11	W16X45	7"	360	2402.0	2683	59010.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-12	3000	14	12	W16X45	7"	360	2465.0	2683	59010.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-13	3000	14	13	W18X55	7-1/2"	360	2702.0	2727	59990.0	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-14	3000	14	14	W18X55	7-1/2"	360	2765.0	2727	59990.0	15'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-3000-14-15	3000	14	15	W16X45	7"	360	2969.0	2683	59010.0	16'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-14-16	3000	14	16	W16X45	7"	360	3040.0	2683	59010.0	17'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-14-17	3000	14	17	W18X55	7-1/2"	360	3289.0	2727	59990.0	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-14-18	3000	14	18	W18X55	7-1/2"	360	3360.0	2727	59990.0	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-14-19	3000	14	19	W18X55	7-1/2"	360	3429.0	2727	59990.0	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-14-20	3000	14	20	W18X55	7-1/2"	360	3500.0	2727	59990.0	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-8	3000	15	8	W18X55	7-1/2"	360	2428.0	2941	64687.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-9	3000	15	9	W18X55	7-1/2"	360	2499.0	2941	64687.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-10	3000	15	10	W18X55	7-1/2"	360	2570.0	2941	64687.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-11	3000	15	11	W18X55	7-1/2"	360	2624.0	2941	64687.5	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-12	3000	15	12	W18X55	7-1/2"	360	2695.0	2941	64687.5	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-13	3000	15	13	W18X55	7-1/2"	360	3064.0	2941	64687.5	14'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-14	3000	15	14	W18X55	7-1/2"	360	3135.0	2941	64687.5	15'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-15	3000	15	15	W18X55	7-1/2"	360	3204.0	2941	64687.5	16'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-16	3000	15	16	W18X55	7-1/2"	360	3275.0	2941	64687.5	17'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-15-17	3000	15	17	W18X55	7-1/2"	360	4016.0	2696	64687.5	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-15-18	3000	15	18	W18X55	7-1/2"	360	4095.0	2696	64687.5	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-15-19	3000	15	19	W18X55	7-1/2"	360	4171.0	2696	64687.5	20'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-15-20	3000	15	20	W18X55	7-1/2"	360	4250.0	2696	64687.5	21'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-16-8	3000	16	8	W18X55	7-1/2"	360	2483.0	3157	69440.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-9	3000	16	9	W18X55	7-1/2"	360	2554.0	3157	69440.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-10	3000	16	10	W18X55	7-1/2"	360	2625.0	3157	69440.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-11	3000	16	11	W18X55	7-1/2"	360	2679.0	3157	69440.0	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-16-12	3000	16	12	W18X55	7-1/2"	360	2750.0	3157	69440.0	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-13	3000	16	13	W18X55	7-1/2"	360	3119.0	3157	69440.0	14'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-14	3000	16	14	W18X55	7-1/2"	360	3190.0	3157	69440.0	15'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-15	3000	16	15	W18X55	7-1/2"	360	3259.0	3157	69440.0	16'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-16	3000	16	16	W18X55	7-1/2"	360	3330.0	3157	69440.0	17'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-16-17	3000	16	17	W18X55	7-1/2"	360	4071.0	2894	69440.0	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-16-18	3000	16	18	W18X55	7-1/2"	360	4150.0	2894	69440.0	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-16-19	3000	16	19	W18X55	7-1/2"	360	4226.0	2894	69440.0	20'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-16-20	3000	16	20	W18X55	7-1/2"	360	4305.0	2894	69440.0	21'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-8	3000	17	8	W18X55	7-1/2"	360	2823.0	3375	74247.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-17-9	3000	17	9	W18X55	7-1/2"	360	2894.0	3375	74247.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-17-10	3000	17	10	W18X55	7-1/2"	360	2965.0	3375	74247.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-17-11	3000	17	11	W18X55	7-1/2"	360	3034.0	3375	74247.5	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-17-12	3000	17	12	W18X55	7-1/2"	360	3105.0	3375	74247.5	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-17-13	3000	17	13	W18X55	7-1/2"	360	3811.0	3094	74247.5	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-14	3000	17	14	W18X55	7-1/2"	360	3895.0	3094	74247.5	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-15	3000	17	15	W18X55	7-1/2"	360	3966.0	3094	74247.5	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-16	3000	17	16	W18X55	7-1/2"	360	4045.0	3094	74247.5	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-17	3000	17	17	W18X55	7-1/2"	360	4625.0	3094	74247.5	18'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-18	3000	17	18	W18X55	7-1/2"	360	4720.0	3094	74247.5	19'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-19	3000	17	19	W18X55	7-1/2"	360	4815.0	3094	74247.5	20'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-17-20	3000	17	20	W18X55	7-1/2"	360	4910.0	3094	74247.5	21'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-18-8	3000	18	8	W18X55	7-1/2"	360	2878.0	3596	79110.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-18-9	3000	18	9	W18X55	7-1/2"	360	2949.0	3596	79110.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-18-10	3000	18	10	W18X55	7-1/2"	360	3020.0	3596	79110.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-18-11	3000	18	11	W18X55	7-1/2"	360	3089.0	3596	79110.0	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-18-12	3000	18	12	W18X55	7-1/2"	360	3160.0	3596	79110.0	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-18-13	3000	18	13	W18X55	7-1/2"	360	3866.0	3297	79110.0	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-14	3000	18	14	W18X55	7-1/2"	360	3945.0	3297	79110.0	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-15	3000	18	15	W18X55	7-1/2"	360	4021.0	3297	79110.0	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-16	3000	18	16	W18X55	7-1/2"	360	4100.0	3297	79110.0	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-17	3000	18	17	W18X55	7-1/2"	360	4680.0	3297	79110.0	18'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-18	3000	18	18	W18X55	7-1/2"	360	4775.0	3297	79110.0	19'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-19	3000	18	19	W18X55	7-1/2"	360	4870.0	3297	79110.0	20'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-18-20	3000	18	20	W18X55	7-1/2"	360	4965.0	3297	79110.0	21'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-8	3000	19	8	W18X55	7-1/2"	360	2933.0	3820	84027.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-19-9	3000	19	9	W18X55	7-1/2"	360	3004.0	3820	84027.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-19-10	3000	19	10	W18X55	7-1/2"	360	3075.0	3820	84027.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-19-11	3000	19	11	W18X55	7-1/2"	360	3761.0	3502	84027.5	12'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-12	3000	19	12	W18X55	7-1/2"	360	3840.0	3502	84027.5	13'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-13	3000	19	13	W21X62	8-1/4"	360	4089.0	3554	85291.0	14'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-14	3000	19	14	W21X62	8-1/4"	360	4168.0	3554	85291.0	15'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-15	3000	19	15	W21X62	8-1/4"	360	4244.0	3554	85291.0	16'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-16	3000	19	16	W21X62	8-1/4"	360	4323.0	3554	85291.0	17'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-3000-19-17	3000	19	17	W21X62	8-1/4"	360	4903.0	3554	85291.0	18'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-18	3000	19	18	W21X62	8-1/4"	360	4998.0	3554	85291.0	19'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-19	3000	19	19	W21X62	8-1/4"	360	5093.0	3554	85291.0	20'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-19-20	3000	19	20	W21X62	8-1/4"	360	5188.0	3554	85291.0	21'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-8	3000	20	8	W18X55	7-1/2"	360	2988.0	4046	89000.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-20-9	3000	20	9	W18X55	7-1/2"	360	3059.0	4046	89000.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-20-10	3000	20	10	W18X55	7-1/2"	360	3130.0	4046	89000.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-3000-20-11	3000	20	11	W18X55	7-1/2"	360	3816.0	3709	89000.0	12'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-12	3000	20	12	W18X55	7-1/2"	360	3895.0	3709	89000.0	13'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-13	3000	20	13	W21X62	8-1/4"	360	4151.0	3767	90400.0	14'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-14	3000	20	14	W21X62	8-1/4"	360	4230.0	3767	90400.0	15'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-15	3000	20	15	W21X62	8-1/4"	360	4306.0	3767	90400.0	16'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-16	3000	20	16	W21X62	8-1/4"	360	4385.0	3767	90400.0	17'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-17	3000	20	17	W21X62	8-1/4"	360	4965.0	3767	90400.0	18'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-18	3000	20	18	W21X62	8-1/4"	360	5060.0	3767	90400.0	19'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-19	3000	20	19	W21X62	8-1/4"	360	5155.0	3767	90400.0	20'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-3000-20-20	3000	20	20	W21X62	8-1/4"	360	5250.0	3767	90400.0	21'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-8-8	4000	8	8	W12X35	6-1/2"	360	1332.0	5340	42720.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-4000-8-9	4000	8	9	W12X35	6-1/2"	360	1386.0	5340	42720.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-4000-8-10	4000	8	10	W12X35	6-1/2"	360	1440.0	5340	42720.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-4000-8-11	4000	8	11	W12X35	6-1/2"	360	1496.0	5340	42720.0	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-4000-8-12	4000	8	12	W12X35	6-1/2"	360	1550.0	5340	42720.0	13'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-8-13	4000	8	13	W12X35	6-1/2"	360	1606.0	5340	42720.0	14'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-8-14	4000	8	14	W12X35	6-1/2"	360	1660.0	5340	42720.0	15'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-8-15	4000	8	15	W12X35	6-1/2"	360	1716.0	5340	42720.0	16'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-8-16	4000	8	16	W12X35	6-1/2"	360	1770.0	5340	42720.0	17'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-8-17	4000	8	17	W16X45	7"	360	2507.0	1957	43040.0	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-8-18	4000	8	18	W16X45	7"	360	2570.0	1957	43040.0	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-8-19	4000	8	19	W16X45	7"	360	2632.0	1957	43040.0	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-8-20	4000	8	20	W16X45	7"	360	2695.0	1957	43040.0	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-9-8	4000	9	8	W12X35	6-1/2"	360	1367.0	6027	48217.5	9'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-9	4000	9	9	W12X35	6-1/2"	360	1421.0	6027	48217.5	10'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-10	4000	9	10	W12X35	6-1/2"	360	1475.0	6027	48217.5	11'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-11	4000	9	11	W12X35	6-1/2"	360	1531.0	6027	48217.5	12'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-12	4000	9	12	W12X35	6-1/2"	360	1585.0	6027	48217.5	13'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-13	4000	9	13	W12X35	6-1/2"	360	1641.0	6027	48217.5	14'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-14	4000	9	14	W12X35	6-1/2"	360	1695.0	6027	48217.5	15'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-15	4000	9	15	W12X35	6-1/2"	360	1751.0	6027	48217.5	16'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-16	4000	9	16	W12X35	6-1/2"	360	1805.0	6027	48217.5	17'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-9-17	4000	9	17	W16X45	7"	360	2552.0	2210	48622.5	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-9-18	4000	9	18	W16X45	7"	360	2615.0	2210	48622.5	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-9-19	4000	9	19	W16X45	7"	360	2677.0	2210	48622.5	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-9-20	4000	9	20	W16X45	7"	360	2740.0	2210	48622.5	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-10-8	4000	10	8	W12X35	6-1/2"	360	1402.0	6718	53750.0	9'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-10-9	4000	10	9	W12X35	6-1/2"	360	1456.0	6718	53750.0	10'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-10	4000	10	10	W12X35	6-1/2"	360	1510.0	6718	53750.0	11'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-11	4000	10	11	W12X35	6-1/2"	360	1566.0	6718	53750.0	12'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-12	4000	10	12	W12X35	6-1/2"	360	1620.0	6718	53750.0	13'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-13	4000	10	13	W12X35	6-1/2"	360	1676.0	6718	53750.0	14'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-14	4000	10	14	W12X35	6-1/2"	360	1730.0	6718	53750.0	15'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-15	4000	10	15	W12X35	6-1/2"	360	1786.0	6718	53750.0	16'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-16	4000	10	16	W12X35	6-1/2"	360	1840.0	6718	53750.0	17'-0"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-10-17	4000	10	17	W16X45	7"	360	2597.0	2466	54250.0	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-10-18	4000	10	18	W16X45	7"	360	2660.0	2466	54250.0	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-10-19	4000	10	19	W16X45	7"	360	2722.0	2466	54250.0	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-10-20	4000	10	20	W16X45	7"	360	2785.0	2466	54250.0	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-8	4000	11	8	W16X45	7"	360	1597.0	7490	59922.5	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-11-9	4000	11	9	W16X45	7"	360	1651.0	7490	59922.5	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-11-10	4000	11	10	W16X45	7"	360	1705.0	7490	59922.5	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-11-11	4000	11	11	W16X45	7"	360	2264.0	2724	59922.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-12	4000	11	12	W16X45	7"	360	2327.0	2724	59922.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-13	4000	11	13	W16X45	7"	360	2392.0	2724	59922.5	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-14	4000	11	14	W16X45	7"	360	2455.0	2724	59922.5	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-15	4000	11	15	W16X45	7"	360	2517.0	2724	59922.5	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-16	4000	11	16	W16X45	7"	360	2580.0	2724	59922.5	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-11-17	4000	11	17	W16X45	7"	360	2974.0	2724	59922.5	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-11-18	4000	11	18	W16X45	7"	360	3045.0	2724	59922.5	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-11-19	4000	11	19	W16X45	7"	360	3114.0	2724	59922.5	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-11-20	4000	11	20	W16X45	7"	360	3185.0	2724	59922.5	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-12-8	4000	12	8	W16X45	7"	360	1642.0	8204	65640.0	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-12-9	4000	12	9	W16X45	7"	360	1696.0	8204	65640.0	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-12-10	4000	12	10	W16X45	7"	360	1750.0	8204	65640.0	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-4000-12-11	4000	12	11	W16X45	7"	360	2309.0	2984	65640.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-12	4000	12	12	W16X45	7"	360	2372.0	2984	65640.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-13	4000	12	13	W16X45	7"	360	2437.0	2984	65640.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-14	4000	12	14	W16X45	7"	360	2500.0	2984	65640.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-15	4000	12	15	W16X45	7"	360	2562.0	2984	65640.0	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-16	4000	12	16	W16X45	7"	360	2625.0	2984	65640.0	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-12-17	4000	12	17	W16X45	7"	360	3019.0	2984	65640.0	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-12-18	4000	12	18	W16X45	7"	360	3090.0	2984	65640.0	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-12-19	4000	12	19	W16X45	7"	360	3159.0	2984	65640.0	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-12-20	4000	12	20	W16X45	7"	360	3230.0	2984	65640.0	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-8	4000	13	8	W16X45	7"	360	2169.0	3246	71402.5	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-9	4000	13	9	W16X45	7"	360	2232.0	3246	71402.5	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-10	4000	13	10	W16X45	7"	360	2295.0	3246	71402.5	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-11	4000	13	11	W16X45	7"	360	2357.0	3246	71402.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-12	4000	13	12	W16X45	7"	360	2420.0	3246	71402.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-13	4000	13	13	W18X55	7-1/2"	360	2647.0	3284	72247.5	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-13-14	4000	13	14	W18X55	7-1/2"	360	2710.0	3284	72247.5	15'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-13-15	4000	13	15	W16X45	7"	360	2924.0	3246	71402.5	16'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-16	4000	13	16	W16X45	7"	360	2995.0	3246	71402.5	17'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-17	4000	13	17	W18X55	7-1/2"	360	3234.0	3284	72247.5	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-18	4000	13	18	W18X55	7-1/2"	360	3305.0	3284	72247.5	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-19	4000	13	19	W18X55	7-1/2"	360	3374.0	3284	72247.5	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-13-20	4000	13	20	W18X55	7-1/2"	360	3445.0	3284	72247.5	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-8	4000	14	8	W16X45	7"	360	2214.0	3510	77210.0	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-9	4000	14	9	W16X45	7"	360	2277.0	3510	77210.0	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-10	4000	14	10	W16X45	7"	360	2340.0	3510	77210.0	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-11	4000	14	11	W16X45	7"	360	2402.0	3510	77210.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-12	4000	14	12	W16X45	7"	360	2465.0	3510	77210.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-13	4000	14	13	W18X55	7-1/2"	360	2702.0	3554	78190.0	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-14	4000	14	14	W18X55	7-1/2"	360	2765.0	3554	78190.0	15'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-4000-14-15	4000	14	15	W16X45	7"	360	2969.0	3510	77210.0	16'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-16	4000	14	16	W16X45	7"	360	3040.0	3510	77210.0	17'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-17	4000	14	17	W18X55	7-1/2"	360	3289.0	3554	78190.0	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-18	4000	14	18	W18X55	7-1/2"	360	3360.0	3554	78190.0	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-19	4000	14	19	W18X55	7-1/2"	360	3429.0	3554	78190.0	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-14-20	4000	14	20	W18X55	7-1/2"	360	3500.0	3554	78190.0	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-8	4000	15	8	W18X55	7-1/2"	360	2428.0	3827	84187.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-9	4000	15	9	W18X55	7-1/2"	360	2499.0	3827	84187.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-15-10	4000	15	10	W18X55	7-1/2"	360	2570.0	3827	84187.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-11	4000	15	11	W18X55	7-1/2"	360	2624.0	3827	84187.5	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-12	4000	15	12	W18X55	7-1/2"	360	2695.0	3827	84187.5	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-13	4000	15	13	W18X55	7-1/2"	360	3064.0	3827	84187.5	14'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-14	4000	15	14	W18X55	7-1/2"	360	3135.0	3827	84187.5	15'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-15	4000	15	15	W18X55	7-1/2"	360	3204.0	3827	84187.5	16'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-16	4000	15	16	W18X55	7-1/2"	360	3275.0	3827	84187.5	17'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-15-17	4000	15	17	W18X55	7-1/2"	360	4016.0	3508	84187.5	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-15-18	4000	15	18	W18X55	7-1/2"	360	4095.0	3508	84187.5	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-15-19	4000	15	19	W18X55	7-1/2"	360	4171.0	3508	84187.5	20'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-15-20	4000	15	20	W18X55	7-1/2"	360	4250.0	3508	84187.5	21'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-16-8	4000	16	8	W18X55	7-1/2"	360	2483.0	4102	90240.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-9	4000	16	9	W18X55	7-1/2"	360	2554.0	4102	90240.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-10	4000	16	10	W18X55	7-1/2"	360	2625.0	4102	90240.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-11	4000	16	11	W18X55	7-1/2"	360	2679.0	4102	90240.0	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-12	4000	16	12	W18X55	7-1/2"	360	2750.0	4102	90240.0	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-13	4000	16	13	W18X55	7-1/2"	360	3119.0	4102	90240.0	14'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-14	4000	16	14	W18X55	7-1/2"	360	3190.0	4102	90240.0	15'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-15	4000	16	15	W18X55	7-1/2"	360	3259.0	4102	90240.0	16'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-16	4000	16	16	W18X55	7-1/2"	360	3330.0	4102	90240.0	17'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-16-17	4000	16	17	W18X55	7-1/2"	360	4071.0	3761	90240.0	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-16-18	4000	16	18	W18X55	7-1/2"	360	4150.0	3761	90240.0	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-16-19	4000	16	19	W18X55	7-1/2"	360	4226.0	3761	90240.0	20'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-16-20	4000	16	20	W18X55	7-1/2"	360	4305.0	3761	90240.0	21'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-8	4000	17	8	W18X55	7-1/2"	360	2823.0	4380	96347.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-17-9	4000	17	9	W18X55	7-1/2"	360	2894.0	4380	96347.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-17-10	4000	17	10	W18X55	7-1/2"	360	2965.0	4380	96347.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-17-11	4000	17	11	W18X55	7-1/2"	360	3034.0	4380	96347.5	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-17-12	4000	17	12	W18X55	7-1/2"	360	3105.0	4380	96347.5	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-17-13	4000	17	13	W18X55	7-1/2"	360	3811.0	4015	96347.5	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-14	4000	17	14	W18X55	7-1/2"	360	3895.0	4015	96347.5	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-15	4000	17	15	W18X55	7-1/2"	360	3966.0	4015	96347.5	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-16	4000	17	16	W18X55	7-1/2"	360	4045.0	4015	96347.5	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-17	4000	17	17	W18X55	7-1/2"	360	4625.0	4015	96347.5	18'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-18	4000	17	18	W18X55	7-1/2"	360	4720.0	4015	96347.5	19'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-19	4000	17	19	W18X55	7-1/2"	360	4815.0	4015	96347.5	20'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-17-20	4000	17	20	W18X55	7-1/2"	360	4910.0	4015	96347.5	21'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-8	4000	18	8	W18X55	7-1/2"	360	2878.0	4660	102510.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-18-9	4000	18	9	W18X55	7-1/2"	360	2949.0	4660	102510.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-18-10	4000	18	10	W18X55	7-1/2"	360	3020.0	4660	102510.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-18-11	4000	18	11	W18X55	7-1/2"	360	3089.0	4660	102510.0	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-18-12	4000	18	12	W18X55	7-1/2"	360	3160.0	4660	102510.0	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-18-13	4000	18	13	W18X55	7-1/2"	360	3866.0	4272	102510.0	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-14	4000	18	14	W18X55	7-1/2"	360	3945.0	4272	102510.0	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-18-15	4000	18	15	W18X55	7-1/2"	360	4021.0	4272	102510.0	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-16	4000	18	16	W18X55	7-1/2"	360	4100.0	4272	102510.0	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-17	4000	18	17	W18X55	7-1/2"	360	4680.0	4272	102510.0	18'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-18	4000	18	18	W18X55	7-1/2"	360	4775.0	4272	102510.0	19'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-19	4000	18	19	W18X55	7-1/2"	360	4870.0	4272	102510.0	20'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-18-20	4000	18	20	W18X55	7-1/2"	360	4965.0	4272	102510.0	21'-6"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-8	4000	19	8	W18X55	7-1/2"	360	2933.0	4942	108727.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-19-9	4000	19	9	W18X55	7-1/2"	360	3004.0	4942	108727.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-19-10	4000	19	10	W18X55	7-1/2"	360	3075.0	4942	108727.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-19-11	4000	19	11	W18X55	7-1/2"	360	3761.0	4531	108727.5	12'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-12	4000	19	12	W18X55	7-1/2"	360	3840.0	4531	108727.5	13'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-13	4000	19	13	W21X62	8-1/4"	360	4089.0	4583	109991.0	14'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-14	4000	19	14	W21X62	8-1/4"	360	4168.0	4583	109991.0	15'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-15	4000	19	15	W21X62	8-1/4"	360	4244.0	4583	109991.0	16'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-16	4000	19	16	W21X62	8-1/4"	360	4323.0	4583	109991.0	17'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-17	4000	19	17	W21X62	8-1/4"	360	4903.0	4583	109991.0	18'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-18	4000	19	18	W21X62	8-1/4"	360	4998.0	4583	109991.0	19'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-19	4000	19	19	W21X62	8-1/4"	360	5093.0	4583	109991.0	20'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-19-20	4000	19	20	W21X62	8-1/4"	360	5188.0	4583	109991.0	21'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-8	4000	20	8	W18X55	7-1/2"	360	2988.0	5227	115000.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-20-9	4000	20	9	W18X55	7-1/2"	360	3059.0	5227	115000.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-4000-20-10	4000	20	10	W18X55	7-1/2"	360	3130.0	5227	115000.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-4000-20-11	4000	20	11	W18X55	7-1/2"	360	3816.0	4792	115000.0	12'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-12	4000	20	12	W18X55	7-1/2"	360	3895.0	4792	115000.0	13'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-13	4000	20	13	W21X62	8-1/4"	360	4151.0	4851	116400.0	14'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-14	4000	20	14	W21X62	8-1/4"	360	4230.0	4851	116400.0	15'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-15	4000	20	15	W21X62	8-1/4"	360	4306.0	4851	116400.0	16'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-16	4000	20	16	W21X62	8-1/4"	360	4385.0	4851	116400.0	17'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-17	4000	20	17	W21X62	8-1/4"	360	4965.0	4851	116400.0	18'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-18	4000	20	18	W21X62	8-1/4"	360	5060.0	4851	116400.0	19'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-19	4000	20	19	W21X62	8-1/4"	360	5155.0	4851	116400.0	20'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-4000-20-20	4000	20	20	W21X62	8-1/4"	360	5250.0	4851	116400.0	21'-9"	24"	29"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4