



Light Duty Freestanding Jib Crane – 351 Series – Up To 2000 Ibs Capacity

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-8-8	500	8	8	W8X18	5 1/4"	360	758.0	889	5776.0	8'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-9	500	8	9	W8X18	5 1/4"	360	786.0	889	5776.0	9'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-10	500	8	10	W8X18	5 1/4"	360	814.0	889	5776.0	10'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-11	500	8	11	W8X18	5 1/4"	360	842.0	889	5776.0	11'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-12	500	8	12	W8X18	5 1/4"	360	870.0	889	5776.0	12'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-13	500	8	13	W8X18	5 1/4"	360	898.0	889	5776.0	13'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-14	500	8	14	W8X18	5 1/4"	360	926.0	889	5776.0	14'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-15	500	8	15	W8X18	5 1/4"	360	954.0	889	5776.0	15'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-16	500	8	16	W8X18	5 1/4"	360	982.0	889	5776.0	16'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-17	500	8	17	W8X18	5 1/4"	360	1010.0	889	5776.0	17'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-18	500	8	18	W8X18	5 1/4"	360	1038.0	889	5776.0	18'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-19	500	8	19	W8X18	5 1/4"	360	1066.0	889	5776.0	19'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-8-20	500	8	20	W8X18	5 1/4"	360	1094.0	889	5776.0	20'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-8	500	9	8	W8X18	5 1/4"	360	776.0	1013	6579.0	8'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-9	500	9	9	W8X18	5 1/4"	360	804.0	1013	6579.0	9'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-10	500	9	10	W8X18	5 1/4"	360	832.0	1013	6579.0	10'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-11	500	9	11	W8X18	5 1/4"	360	860.0	1013	6579.0	11'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-12	500	9	12	W8X18	5 1/4"	360	888.0	1013	6579.0	12'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-13	500	9	13	W8X18	5 1/4"	360	916.0	1013	6579.0	13'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-14	500	9	14	W8X18	5 1/4"	360	944.0	1013	6579.0	14'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-9-15	500	9	15	W8X18	5 1/4"	360	972.0	1013	6579.0	15'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-16	500	9	16	W8X18	5 1/4"	360	1000.0	1013	6579.0	16'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-17	500	9	17	W8X18	5 1/4"	360	1028.0	1013	6579.0	17'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-18	500	9	18	W8X18	5 1/4"	360	1056.0	1013	6579.0	18'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-19	500	9	19	W8X18	5 1/4"	360	1084.0	1013	6579.0	19'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-9-20	500	9	20	W8X18	5 1/4"	360	1112.0	1013	6579.0	20'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-8	500	10	8	W8X18	5 1/4"	360	794.0	1139	7400.0	8'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-9	500	10	9	W8X18	5 1/4"	360	822.0	1139	7400.0	9'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-10	500	10	10	W8X18	5 1/4"	360	850.0	1139	7400.0	10'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-11	500	10	11	W8X18	5 1/4"	360	878.0	1139	7400.0	11'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-12	500	10	12	W8X18	5 1/4"	360	906.0	1139	7400.0	12'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-13	500	10	13	W8X18	5 1/4"	360	934.0	1139	7400.0	13'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-14	500	10	14	W8X18	5 1/4"	360	962.0	1139	7400.0	14'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-15	500	10	15	W8X18	5 1/4"	360	990.0	1139	7400.0	15'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-16	500	10	16	W8X18	5 1/4"	360	1018.0	1139	7400.0	16'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-17	500	10	17	W8X18	5 1/4"	360	1046.0	1139	7400.0	17'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-18	500	10	18	W8X18	5 1/4"	360	1074.0	1139	7400.0	18'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-19	500	10	19	W8X18	5 1/4"	360	1102.0	1139	7400.0	19'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-10-20	500	10	20	W8X18	5 1/4"	360	1130.0	1139	7400.0	20'-8 1/8"	8 5/8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-500-11-8	500	11	8	W8X18	5 1/4"	360	799.0	1030	8239.0	8'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-9	500	11	9	W8X18	5 1/4"	360	845.0	1030	8239.0	9'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-10	500	11	10	W8X18	5 1/4"	360	873.0	1030	8239.0	10'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-11-11	500	11	11	W8X18	5 1/4"	360	901.0	1030	8239.0	11'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-12	500	11	12	W8X18	5 1/4"	360	929.0	1030	8239.0	12'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-13	500	11	13	W8X18	5 1/4"	360	957.0	1030	8239.0	13'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-14	500	11	14	W8X18	5 1/4"	360	985.0	1030	8239.0	14'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-15	500	11	15	W8X18	5 1/4"	360	1013.0	1030	8239.0	15'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-16	500	11	16	W8X18	5 1/4"	360	1041.0	1030	8239.0	16'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-17	500	11	17	W8X18	5 1/4"	360	1069.0	1030	8239.0	17'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-18	500	11	18	W8X18	5 1/4"	360	1097.0	1030	8239.0	18'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-19	500	11	19	W8X18	5 1/4"	360	1125.0	1030	8239.0	19'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-11-20	500	11	20	W8X18	5 1/4"	360	1153.0	1030	8239.0	20'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-8	500	12	8	W8X18	5 1/4"	360	817.0	1137	9096.0	8'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-9	500	12	9	W8X18	5 1/4"	360	863.0	1137	9096.0	9'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-10	500	12	10	W8X18	5 1/4"	360	891.0	1137	9096.0	10'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-11	500	12	11	W8X18	5 1/4"	360	919.0	1137	9096.0	11'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-12	500	12	12	W8X18	5 1/4"	360	947.0	1137	9096.0	12'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-13	500	12	13	W8X18	5 1/4"	360	975.0	1137	9096.0	13'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-14	500	12	14	W8X18	5 1/4"	360	1003.0	1137	9096.0	14'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-15	500	12	15	W8X18	5 1/4"	360	1031.0	1137	9096.0	15'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-16	500	12	16	W8X18	5 1/4"	360	1059.0	1137	9096.0	16'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-17	500	12	17	W8X18	5 1/4"	360	1087.0	1137	9096.0	17'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-18	500	12	18	W8X18	5 1/4"	360	1115.0	1137	9096.0	18'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-12-19	500	12	19	W8X18	5 1/4"	360	1143.0	1137	9096.0	19'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-12-20	500	12	20	W8X18	5 1/4"	360	1171.0	1137	9096.0	20'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-8	500	13	8	W8X18	5 1/4"	360	835.0	1247	9971.0	8'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-9	500	13	9	W8X18	5 1/4"	360	881.0	1247	9971.0	9'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-10	500	13	10	W8X18	5 1/4"	360	909.0	1247	9971.0	10'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-11	500	13	11	W8X18	5 1/4"	360	937.0	1247	9971.0	11'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-12	500	13	12	W8X18	5 1/4"	360	965.0	1247	9971.0	12'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-13	500	13	13	W8X18	5 1/4"	360	993.0	1247	9971.0	13'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-14	500	13	14	W8X18	5 1/4"	360	1021.0	1247	9971.0	14'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-15	500	13	15	W8X18	5 1/4"	360	1049.0	1247	9971.0	15'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-16	500	13	16	W8X18	5 1/4"	360	1077.0	1247	9971.0	16'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-17	500	13	17	W8X18	5 1/4"	360	1105.0	1247	9971.0	17'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-18	500	13	18	W8X18	5 1/4"	360	1133.0	1247	9971.0	18'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-19	500	13	19	W8X18	5 1/4"	360	1161.0	1247	9971.0	19'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-13-20	500	13	20	W8X18	5 1/4"	360	1189.0	1247	9971.0	20'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-8	500	14	8	W8X18	5 1/4"	360	853.0	1358	10864.0	8'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-9	500	14	9	W8X18	5 1/4"	360	899.0	1358	10864.0	9'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-10	500	14	10	W8X18	5 1/4"	360	927.0	1358	10864.0	10'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-11	500	14	11	W8X18	5 1/4"	360	955.0	1358	10864.0	11'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-12	500	14	12	W8X18	5 1/4"	360	983.0	1358	10864.0	12'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-13	500	14	13	W8X18	5 1/4"	360	1011.0	1358	10864.0	13'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-14	500	14	14	W8X18	5 1/4"	360	1039.0	1358	10864.0	14'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-15	500	14	15	W8X18	5 1/4"	360	1067.0	1358	10864.0	15'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-14-16	500	14	16	W8X18	5 1/4"	360	1095.0	1358	10864.0	16'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-17	500	14	17	W8X18	5 1/4"	360	1123.0	1358	10864.0	17'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-18	500	14	18	W8X18	5 1/4"	360	1151.0	1358	10864.0	18'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-19	500	14	19	W8X18	5 1/4"	360	1179.0	1358	10864.0	19'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-14-20	500	14	20	W8X18	5 1/4"	360	1207.0	1358	10864.0	20'-8 1/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-8	500	15	8	W10X26	5 3/4"	360	1003.0	1585	12675.0	8'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-9	500	15	9	W10X26	5 3/4"	360	1049.0	1585	12675.0	9'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-10	500	15	10	W10X26	5 3/4"	360	1077.0	1585	12675.0	10'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-11	500	15	11	W10X26	5 3/4"	360	1105.0	1585	12675.0	11'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-12	500	15	12	W10X26	5 3/4"	360	1133.0	1585	12675.0	12'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-13	500	15	13	W10X26	5 3/4"	360	1161.0	1585	12675.0	13'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-14	500	15	14	W10X26	5 3/4"	360	1189.0	1585	12675.0	14'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-15	500	15	15	W10X26	5 3/4"	360	1217.0	1585	12675.0	15'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-16	500	15	16	W10X26	5 3/4"	360	1245.0	1585	12675.0	16'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-17	500	15	17	W10X26	5 3/4"	360	1273.0	1585	12675.0	17'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-18	500	15	18	W10X26	5 3/4"	360	1301.0	1585	12675.0	18'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-19	500	15	19	W10X26	5 3/4"	360	1329.0	1585	12675.0	19'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-15-20	500	15	20	W10X26	5 3/4"	360	1357.0	1585	12675.0	20'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-8	500	16	8	W10X26	5 3/4"	360	1029.0	1716	13728.0	8'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-9	500	16	9	W10X26	5 3/4"	360	1075.0	1716	13728.0	9'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-10	500	16	10	W10X26	5 3/4"	360	1103.0	1716	13728.0	10'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-11	500	16	11	W10X26	5 3/4"	360	1131.0	1716	13728.0	11'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-16-12	500	16	12	W10X26	5 3/4"	360	1159.0	1716	13728.0	12'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-13	500	16	13	W10X26	5 3/4"	360	1187.0	1716	13728.0	13'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-14	500	16	14	W10X26	5 3/4"	360	1215.0	1716	13728.0	14'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-15	500	16	15	W10X26	5 3/4"	360	1243.0	1716	13728.0	15'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-16	500	16	16	W10X26	5 3/4"	360	1271.0	1716	13728.0	16'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-17	500	16	17	W10X26	5 3/4"	360	1299.0	1716	13728.0	17'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-18	500	16	18	W10X26	5 3/4"	360	1327.0	1716	13728.0	18'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-19	500	16	19	W10X26	5 3/4"	360	1355.0	1716	13728.0	19'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-16-20	500	16	20	W10X26	5 3/4"	360	1383.0	1716	13728.0	20'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-8	500	17	8	W10X26	5 3/4"	360	1055.0	1851	14807.0	8'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-9	500	17	9	W10X26	5 3/4"	360	1101.0	1851	14807.0	9'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-10	500	17	10	W10X26	5 3/4"	360	1129.0	1851	14807.0	10'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-11	500	17	11	W10X26	5 3/4"	360	1157.0	1851	14807.0	11'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-12	500	17	12	W10X26	5 3/4"	360	1185.0	1851	14807.0	12'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-13	500	17	13	W10X26	5 3/4"	360	1213.0	1851	14807.0	13'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-14	500	17	14	W10X26	5 3/4"	360	1241.0	1851	14807.0	14'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-15	500	17	15	W10X26	5 3/4"	360	1269.0	1851	14807.0	15'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-16	500	17	16	W10X26	5 3/4"	360	1297.0	1851	14807.0	16'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-17	500	17	17	W10X26	5 3/4"	360	1325.0	1851	14807.0	17'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-18	500	17	18	W10X26	5 3/4"	360	1353.0	1851	14807.0	18'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-19	500	17	19	W10X26	5 3/4"	360	1381.0	1851	14807.0	19'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-17-20	500	17	20	W10X26	5 3/4"	360	1409.0	1851	14807.0	20'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-18-8	500	18	8	W10X26	5 3/4"	360	1081.0	1989	15912.0	8'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-9	500	18	9	W10X26	5 3/4"	360	1127.0	1989	15912.0	9'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-10	500	18	10	W10X26	5 3/4"	360	1155.0	1989	15912.0	10'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-11	500	18	11	W10X26	5 3/4"	360	1183.0	1989	15912.0	11'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-12	500	18	12	W10X26	5 3/4"	360	1211.0	1989	15912.0	12'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-13	500	18	13	W10X26	5 3/4"	360	1239.0	1989	15912.0	13'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-14	500	18	14	W10X26	5 3/4"	360	1267.0	1989	15912.0	14'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-15	500	18	15	W10X26	5 3/4"	360	1295.0	1989	15912.0	15'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-16	500	18	16	W10X26	5 3/4"	360	1323.0	1989	15912.0	16'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-17	500	18	17	W10X26	5 3/4"	360	1351.0	1989	15912.0	17'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-18	500	18	18	W10X26	5 3/4"	360	1378.0	1989	15912.0	18'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-19	500	18	19	W10X26	5 3/4"	360	1407.0	1989	15912.0	19'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-18-20	500	18	20	W10X26	5 3/4"	360	1435.0	1989	15912.0	20'-10 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-8	500	19	8	W12X30	6 1/2"	360	1187.0	2221	17765.0	9'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-9	500	19	9	W12X30	6 1/2"	360	1233.0	2221	17765.0	10'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-10	500	19	10	W12X30	6 1/2"	360	1261.0	2221	17765.0	11'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-11	500	19	11	W12X30	6 1/2"	360	1289.0	2221	17765.0	12'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-12	500	19	12	W12X30	6 1/2"	360	1317.0	2221	17765.0	13'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-13	500	19	13	W12X30	6 1/2"	360	1345.0	2221	17765.0	14'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-14	500	19	14	W12X30	6 1/2"	360	1373.0	2221	17765.0	15'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-15	500	19	15	W12X30	6 1/2"	360	1401.0	2221	17765.0	16'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-16	500	19	16	W12X30	6 1/2"	360	1429.0	2221	17765.0	17'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-500-19-17	500	19	17	W12X30	6 1/2"	360	1457.0	2221	17765.0	18'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-18	500	19	18	W12X30	6 1/2"	360	1484.0	2221	17765.0	19'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-19	500	19	19	W12X30	6 1/2"	360	1513.0	2221	17765.0	20'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-19-20	500	19	20	W12X30	6 1/2"	360	1541.0	2221	17765.0	21'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-8	500	20	8	W12X30	6 1/2"	360	1217.0	2375	19000.0	9'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-9	500	20	9	W12X30	6 1/2"	360	1263.0	2375	19000.0	10'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-10	500	20	10	W12X30	6 1/2"	360	1291.0	2375	19000.0	11'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-11	500	20	11	W12X30	6 1/2"	360	1319.0	2375	19000.0	12'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-12	500	20	12	W12X30	6 1/2"	360	1347.0	2375	19000.0	13'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-13	500	20	13	W12X30	6 1/2"	360	1375.0	2375	19000.0	14'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-14	500	20	14	W12X30	6 1/2"	360	1403.0	2375	19000.0	15'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-15	500	20	15	W12X30	6 1/2"	360	1431.0	2375	19000.0	16'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-16	500	20	16	W12X30	6 1/2"	360	1459.0	2375	19000.0	17'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-17	500	20	17	W12X30	6 1/2"	360	1487.0	2375	19000.0	18'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-18	500	20	18	W12X30	6 1/2"	360	1514.0	2375	19000.0	19'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-19	500	20	19	W12X30	6 1/2"	360	1543.0	2375	19000.0	20'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-500-20-20	500	20	20	W12X30	6 1/2"	360	1571.0	2375	19000.0	21'-0 3/8"	12 3/4"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-8	1000	8	8	W10X26	5-3/4"	360	828.0	1728	11232.0	8'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-8-9	1000	8	9	W10X26	5-3/4"	360	867.0	1728	11232.0	9'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-8-10	1000	8	10	W10X26	5-3/4"	360	896.0	1728	11232.0	10'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-8-11	1000	8	11	W8X18	5-1/4"	360	1040.0	1372	10976.0	11'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-12	1000	8	12	W8X18	5-1/4"	360	1074.0	1372	10976.0	12'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturing Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-8-13	1000	8	13	W8X18	5-1/4"	360	1107.0	1372	10976.0	13'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-14	1000	8	14	W8X18	5-1/4"	360	1141.0	1372	10976.0	14'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-15	1000	8	15	W8X18	5-1/4"	360	1175.0	1372	10976.0	15'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-16	1000	8	16	W8X18	5-1/4"	360	1209.0	1372	10976.0	16'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-17	1000	8	17	W8X18	5-1/4"	360	1242.0	1372	10976.0	17'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-18	1000	8	18	W8X18	5-1/4"	360	1276.0	1372	10976.0	18'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-19	1000	8	19	W10X26	5-3/4"	360	1383.0	1404	11232.0	19'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-8-20	1000	8	20	W10X26	5-3/4"	360	1417.0	1404	11232.0	20'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-8	1000	9	8	W10X26	5-3/4"	360	854.0	1962	12753.0	8'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-9-9	1000	9	9	W10X26	5-3/4"	360	893.0	1962	12753.0	9'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-9-10	1000	9	10	W10X26	5-3/4"	360	922.0	1962	12753.0	10'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-9-11	1000	9	11	W8X18	5-1/4"	360	1058.0	1554	12429.0	11'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-12	1000	9	12	W8X18	5-1/4"	360	1092.0	1554	12429.0	12'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-13	1000	9	13	W8X18	5-1/4"	360	1125.0	1554	12429.0	13'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-14	1000	9	14	W8X18	5-1/4"	360	1159.0	1554	12429.0	14'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-15	1000	9	15	W8X18	5-1/4"	360	1193.0	1554	12429.0	15'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-16	1000	9	16	W8X18	5-1/4"	360	1227.0	1554	12429.0	16'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-17	1000	9	17	W8X18	5-1/4"	360	1260.0	1554	12429.0	17'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-18	1000	9	18	W8X18	5-1/4"	360	1294.0	1554	12429.0	18'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-19	1000	9	19	W10X26	5-3/4"	360	1409.0	1594	12753.0	19'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-9-20	1000	9	20	W10X26	5-3/4"	360	1443.0	1594	12753.0	20'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-8	1000	10	8	W10X26	5-3/4"	360	880.0	2200	14300.0	8'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-10-9	1000	10	9	W10X26	5-3/4"	360	919.0	2200	14300.0	9'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-10-10	1000	10	10	W10X26	5-3/4"	360	948.0	2200	14300.0	10'-10"	8"	14"	26"	30"	6	4' X 4' X 4'	3'-6 1/4"	4x3x3
351-1000-10-11	1000	10	11	W8X18	5-1/4"	360	1076.0	1738	13900.0	11'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-12	1000	10	12	W8X18	5-1/4"	360	1110.0	1738	13900.0	12'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-13	1000	10	13	W8X18	5-1/4"	360	1143.0	1738	13900.0	13'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-14	1000	10	14	W8X18	5-1/4"	360	1177.0	1738	13900.0	14'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-15	1000	10	15	W8X18	5-1/4"	360	1211.0	1738	13900.0	15'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-16	1000	10	16	W8X18	5-1/4"	360	1245.0	1738	13900.0	16'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-17	1000	10	17	W8X18	5-1/4"	360	1278.0	1738	13900.0	17'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-18	1000	10	18	W8X18	5-1/4"	360	1312.0	1738	13900.0	18'-8"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-19	1000	10	19	W10X26	5-3/4"	360	1435.0	1788	14300.0	19'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-10-20	1000	10	20	W10X26	5-3/4"	360	1469.0	1788	14300.0	20'-10"	12"	15"	32"	36"	6	4' X 4' X 4'	4'-0 1/4"	5x3x3
351-1000-11-8	1000	11	8	W8X18	5-1/4"	360	1011.0	1924	15389.0	8'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-9	1000	11	9	W8X18	5-1/4"	360	1045.0	1924	15389.0	9'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-10	1000	11	10	W8X18	5-1/4"	360	1079.0	1924	15389.0	10'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-11	1000	11	11	W10X26	5-3/4"	360	1218.0	1984	15873.0	11'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-12	1000	11	12	W10X26	5-3/4"	360	1252.0	1984	15873.0	12'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-13	1000	11	13	W10X26	5-3/4"	360	1286.0	1984	15873.0	13'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-14	1000	11	14	W10X26	5-3/4"	360	1320.0	1984	15873.0	14'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-15	1000	11	15	W10X26	5-3/4"	360	1353.0	1984	15873.0	15'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-16	1000	11	16	W10X26	5-3/4"	360	1387.0	1984	15873.0	16'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-17	1000	11	17	W10X26	5-3/4"	360	1529.0	1984	15873.0	17'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-11-18	1000	11	18	W10X26	5-3/4"	360	1573.0	1984	15873.0	18'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-11-19	1000	11	19	W10X26	5-3/4"	360	1994.0	1984	15873.0	19'-10"	16"	15"	32"	36"	6	4.5' X 4.5' X 4'	5'-0 1/4"	6x3x3
351-1000-11-20	1000	11	20	W10X26	5-3/4"	360	2049.0	1984	15873.0	20'-10"	16"	15"	32"	36"	6	4.5' X 4.5' X 4'	5'-0 1/4"	6x3x3
351-1000-12-8	1000	12	8	W8X18	5-1/4"	360	1011.0	2112	16896.0	8'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-9	1000	12	9	W8X18	5-1/4"	360	1045.0	2112	16896.0	9'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-10	1000	12	10	W8X18	5-1/4"	360	1079.0	2112	16896.0	10'-8"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-11	1000	12	11	W10X26	5-3/4"	360	1218.0	2184	17472.0	11'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-12	1000	12	12	W10X26	5-3/4"	360	1252.0	2184	17472.0	12'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-13	1000	12	13	W10X26	5-3/4"	360	1286.0	2184	17472.0	13'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-14	1000	12	14	W10X26	5-3/4"	360	1320.0	2184	17472.0	14'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-15	1000	12	15	W10X26	5-3/4"	360	1353.0	2184	17472.0	15'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-16	1000	12	16	W10X26	5-3/4"	360	1387.0	2184	17472.0	16'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-17	1000	12	17	W10X26	5-3/4"	360	1529.0	2184	17472.0	17'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-18	1000	12	18	W10X26	5-3/4"	360	1573.0	2184	17472.0	18'-10"	12"	15"	32"	36"	6	4.5' X 4.5' X 4'	4'-0 1/4"	5x3x3
351-1000-12-19	1000	12	19	W10X26	5-3/4"	360	1994.0	2184	17472.0	19'-10"	16"	15"	32"	36"	6	4.5' X 4.5' X 4'	5'-0 1/4"	6x3x3
351-1000-12-20	1000	12	20	W10X26	5-3/4"	360	2049.0	2184	17472.0	20'-10"	16"	15"	32"	36"	6	4.5' X 4.5' X 4'	5'-0 1/4"	6x3x3
351-1000-13-8	1000	13	8	W10X26	5-3/4"	360	1143.0	2387	19097.0	8'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-9	1000	13	9	W10X26	5-3/4"	360	1277.0	2387	19097.0	9'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-10	1000	13	10	W10X26	5-3/4"	360	1211.0	2387	19097.0	10'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-11	1000	13	11	W10X26	5-3/4"	360	1358.0	2387	19097.0	11'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-12	1000	13	12	W10X26	5-3/4"	360	1402.0	2387	19097.0	12'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-13	1000	13	13	W12X30	6-1/2"	360	1506.0	2430	19435.0	14'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-13-14	1000	13	14	W12X30	6-1/2"	360	1550.0	2430	19435.0	15'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-15	1000	13	15	W12X30	6-1/2"	360	1598.0	2430	19435.0	16'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-16	1000	13	16	W12X30	6-1/2"	360	1642.0	2430	19435.0	17'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-13-17	1000	13	17	W12X30	6-1/2"	360	1962.0	2430	19435.0	18'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-13-18	1000	13	18	W12X30	6-1/2"	360	2017.0	2430	19435.0	19'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-13-19	1000	13	19	W12X30	6-1/2"	360	2072.0	2430	19435.0	20'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-13-20	1000	13	20	W12X30	6-1/2"	360	2127.0	2430	19435.0	21'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-14-8	1000	14	8	W10X26	5-3/4"	360	1169.0	2594	20748.0	8'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-9	1000	14	9	W10X26	5-3/4"	360	1203.0	2594	20748.0	9'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-10	1000	14	10	W10X26	5-3/4"	360	1237.0	2594	20748.0	10'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-11	1000	14	11	W10X26	5-3/4"	360	1384.0	2594	20748.0	11'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-12	1000	14	12	W10X26	5-3/4"	360	1428.0	2594	20748.0	12'-10"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-13	1000	14	13	W12X30	6-1/2"	360	1536.0	2643	21140.0	14'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-14	1000	14	14	W12X30	6-1/2"	360	1580.0	2643	21140.0	15'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-15	1000	14	15	W12X30	6-1/2"	360	1628.0	2643	21140.0	16'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-16	1000	14	16	W12X30	6-1/2"	360	1672.0	2643	21140.0	17'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-14-17	1000	14	17	W12X30	6-1/2"	360	1992.0	2643	21140.0	18'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-14-18	1000	14	18	W12X30	6-1/2"	360	2047.0	2643	21140.0	19'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-14-19	1000	14	19	W12X30	6-1/2"	360	2102.0	2643	21140.0	20'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-14-20	1000	14	20	W12X30	6-1/2"	360	2157.0	2643	21140.0	21'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-8	1000	15	8	W12X30	6-1/2"	360	1247.0	2860	22875.0	9'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-15-9	1000	15	9	W12X30	6-1/2"	360	1291.0	2860	22875.0	10'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturing Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-15-10	1000	15	10	W12X30	6-1/2"	360	1335.0	2860	22875.0	11'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-15-11	1000	15	11	W12X30	6-1/2"	360	1481.0	2860	22875.0	12'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-15-12	1000	15	12	W12X30	6-1/2"	360	1535.0	2860	22875.0	13'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-15-13	1000	15	13	W12X30	6-1/2"	360	1805.0	2860	22875.0	14'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-14	1000	15	14	W12X30	6-1/2"	360	1860.0	2860	22875.0	15'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-15	1000	15	15	W12X30	6-1/2"	360	1920.0	2860	22875.0	16'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-16	1000	15	16	W12X30	6-1/2"	360	1975.0	2860	22875.0	17'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-17	1000	15	17	W16X45	7"	360	2270.0	3070	24562.5	18'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-18	1000	15	18	W16X45	7"	360	2325.0	3070	24562.5	19'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-19	1000	15	19	W16X45	7"	360	2380.0	3070	24562.5	20'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-15-20	1000	15	20	W16X45	7"	360	2435.0	3070	24562.5	21'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-8	1000	16	8	W12X30	6-1/2"	360	1277.0	3080	24640.0	9'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-16-9	1000	16	9	W12X30	6-1/2"	360	1321.0	3080	24640.0	10'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-16-10	1000	16	10	W12X30	6-1/2"	360	1365.0	3080	24640.0	11'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-16-11	1000	16	11	W12X30	6-1/2"	360	1511.0	3080	24640.0	12'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-16-12	1000	16	12	W12X30	6-1/2"	360	1555.0	3080	24640.0	13'-0"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-16-13	1000	16	13	W12X30	6-1/2"	360	1835.0	3080	24640.0	14'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-14	1000	16	14	W12X30	6-1/2"	360	1890.0	3080	24640.0	15'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-15	1000	16	15	W12X30	6-1/2"	360	1950.0	3080	24640.0	16'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-16	1000	16	16	W12X30	6-1/2"	360	2005.0	3080	24640.0	17'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-17	1000	16	17	W16X45	7"	360	2315.0	3320	26560.0	18'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-18	1000	16	18	W16X45	7"	360	2370.0	3320	26560.0	19'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-16-19	1000	16	19	W16X45	7"	360	2425.0	3320	26560.0	20'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-16-20	1000	16	20	W16X45	7"	360	2480.0	3320	26560.0	21'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-8	1000	17	8	W12X30	6-1/2"	360	1407.0	3304	26435.0	9'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-17-9	1000	17	9	W12X30	6-1/2"	360	1451.0	3304	26435.0	10'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-17-10	1000	17	10	W12X30	6-1/2"	360	1495.0	3304	26435.0	11'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-17-11	1000	17	11	W12X30	6-1/2"	360	1760.0	3304	26435.0	12'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-12	1000	17	12	W12X30	6-1/2"	360	1815.0	3304	26435.0	13'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-13	1000	17	13	W16X45	7"	360	2140.0	3575	28602.5	14'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-14	1000	17	14	W16X45	7"	360	2195.0	3575	28602.5	15'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-15	1000	17	15	W16X45	7"	360	2250.0	3575	28602.5	16'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-16	1000	17	16	W16X45	7"	360	2305.0	3575	28602.5	17'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-17	1000	17	17	W16X45	7"	360	2360.0	3575	28602.5	18'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-18	1000	17	18	W16X45	7"	360	2415.0	3575	28602.5	19'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-17-19	1000	17	19	W16X45	7"	360	3012.0	1300	28602.5	20'-4"	16"	19"	44"	48"	12	5.5' X 5.5' X 4'	5'-0 1/4"	6x3x3
351-1000-17-20	1000	17	20	W16X45	7"	360	3075.0	1300	28602.5	21'-4"	16"	19"	44"	48"	12	5.5' X 5.5' X 4'	5'-0 1/4"	6x3x3
351-1000-18-8	1000	18	8	W12X30	6-1/2"	360	1437.0	3533	28260.0	9'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-18-9	1000	18	9	W12X30	6-1/2"	360	1481.0	3533	28260.0	10'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-18-10	1000	18	10	W12X30	6-1/2"	360	1525.0	3533	28260.0	11'-0"	12"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-1000-18-11	1000	18	11	W12X30	6-1/2"	360	1790.0	3533	28260.0	12'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-12	1000	18	12	W12X30	6-1/2"	360	1845.0	3533	28260.0	13'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-13	1000	18	13	W16X45	7"	360	2185.0	3836	30690.0	14'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-14	1000	18	14	W16X45	7"	360	2240.0	3836	30690.0	15'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-18-15	1000	18	15	W16X45	7"	360	2295.0	3836	30690.0	16'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-16	1000	18	16	W16X45	7"	360	2350.0	3836	30690.0	17'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-17	1000	18	17	W16X45	7"	360	2405.0	3836	30690.0	18'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-18	1000	18	18	W16X45	7"	360	2460.0	3836	30690.0	19'-4"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-1000-18-19	1000	18	19	W16X45	7"	360	3057.0	1395	30690.0	20'-4"	16"	19"	44"	48"	12	5.5' X 5.5' X 4'	5'-0 1/4"	6x3x3
351-1000-18-20	1000	18	20	W16X45	7"	360	3120.0	1395	30690.0	21'-4"	16"	19"	44"	48"	12	5.5' X 5.5' X 4'	5'-0 1/4"	6x3x3
351-1000-19-8	1000	19	8	W12X30	6-1/2"	360	1655.0	3764	30115.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-9	1000	19	9	W12X30	6-1/2"	360	1710.0	3764	30115.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-10	1000	19	10	W12X30	6-1/2"	360	1765.0	3764	30115.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-11	1000	19	11	W16X45	7"	360	2120.0	4103	32822.5	12'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-12	1000	19	12	W16X45	7"	360	2175.0	4103	32822.5	13'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-13	1000	19	13	W16X45	7"	360	2230.0	4103	32822.5	14'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-14	1000	19	14	W16X45	7"	360	2285.0	4103	32822.5	15'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-19-15	1000	19	15	W16X45	7"	360	2852.0	1492	32822.5	16'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-19-16	1000	19	16	W16X45	7"	360	2915.0	1492	32822.5	17'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-19-17	1000	19	17	W16X45	7"	360	2977.0	1492	32822.5	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-19-18	1000	19	18	W16X45	7"	360	3040.0	1492	32822.5	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-19-19	1000	19	19	W16X45	7"	360	3104.0	1492	32822.5	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-19-20	1000	19	20	W16X45	7"	360	3167.0	1492	32822.5	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-8	1000	20	8	W12X30	6-1/2"	360	1685.0	4000	32000.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-9	1000	20	9	W12X30	6-1/2"	360	1740.0	4000	32000.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-10	1000	20	10	W12X30	6-1/2"	360	1795.0	4000	32000.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-1000-20-11	1000	20	11	W16X45	7"	360	2165.0	4375	35000.0	12'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-12	1000	20	12	W16X45	7"	360	2220.0	4375	35000.0	13'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-13	1000	20	13	W16X45	7"	360	2275.0	4375	35000.0	14'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-14	1000	20	14	W16X45	7"	360	2330.0	4375	35000.0	15'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-1000-20-15	1000	20	15	W16X45	7"	360	2897.0	1591	35000.0	16'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-16	1000	20	16	W16X45	7"	360	2960.0	1591	35000.0	17'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-17	1000	20	17	W16X45	7"	360	3022.0	1591	35000.0	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-18	1000	20	18	W16X45	7"	360	3085.0	1591	35000.0	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-19	1000	20	19	W16X45	7"	360	3149.0	1591	35000.0	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-1000-20-20	1000	20	20	W16X45	7"	360	3212.0	1591	35000.0	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-8-8	2000	8	8	W10X26	5-3/4"	360	981.0	2704	21632.0	8'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-9	2000	8	9	W10X26	5-3/4"	360	1031.0	2704	21632.0	9'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-10	2000	8	10	W10X26	5-3/4"	360	1081.0	2704	21632.0	10'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-11	2000	8	11	W10X26	5-3/4"	360	1098.0	2704	21632.0	11'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-12	2000	8	12	W10X26	5-3/4"	360	1148.0	2704	21632.0	12'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-13	2000	8	13	W10X26	5-3/4"	360	1166.0	2704	21632.0	13'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-14	2000	8	14	W10X26	5-3/4"	360	1216.0	2704	21632.0	14'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-15	2000	8	15	W10X26	5-3/4"	360	1490.0	2704	21632.0	15'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-16	2000	8	16	W10X26	5-3/4"	360	1540.0	2704	21632.0	16'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-8-17	2000	8	17	W10X26	5-3/4"	360	1770.0	2704	21632.0	17'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-8-18	2000	8	18	W10X26	5-3/4"	360	1824.0	2704	21632.0	18'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-8-19	2000	8	19	W10X26	5-3/4"	360	1880.0	2704	21632.0	19'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-8-20	2000	8	20	W10X26	5-3/4"	360	1934.0	2704	21632.0	20'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-9-8	2000	9	8	W10X26	5-3/4"	360	1007.0	3057	24453.0	8'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-9	2000	9	9	W10X26	5-3/4"	360	1057.0	3057	24453.0	9'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-10	2000	9	10	W10X26	5-3/4"	360	1107.0	3057	24453.0	10'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-11	2000	9	11	W10X26	5-3/4"	360	1124.0	3057	24453.0	11'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-12	2000	9	12	W10X26	5-3/4"	360	1174.0	3057	24453.0	12'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-13	2000	9	13	W10X26	5-3/4"	360	1192.0	3057	24453.0	13'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-14	2000	9	14	W10X26	5-3/4"	360	1242.0	3057	24453.0	14'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-15	2000	9	15	W10X26	5-3/4"	360	1516.0	3057	24453.0	15'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-16	2000	9	16	W10X26	5-3/4"	360	1566.0	3057	24453.0	16'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-9-17	2000	9	17	W10X26	5-3/4"	360	1796.0	3057	24453.0	17'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-9-18	2000	9	18	W10X26	5-3/4"	360	1850.0	3057	24453.0	18'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-9-19	2000	9	19	W10X26	5-3/4"	360	1906.0	3057	24453.0	19'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-9-20	2000	9	20	W10X26	5-3/4"	360	1960.0	3057	24453.0	20'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-10-8	2000	10	8	W10X26	5-3/4"	360	1033.0	3413	27300.0	8'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-9	2000	10	9	W10X26	5-3/4"	360	1083.0	3413	27300.0	9'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-10	2000	10	10	W10X26	5-3/4"	360	1133.0	3413	27300.0	10'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-11	2000	10	11	W10X26	5-3/4"	360	1150.0	3413	27300.0	11'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-12	2000	10	12	W10X26	5-3/4"	360	1200.0	3413	27300.0	12'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-13	2000	10	13	W10X26	5-3/4"	360	1218.0	3413	27300.0	13'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-14	2000	10	14	W10X26	5-3/4"	360	1268.0	3413	27300.0	14'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-15	2000	10	15	W10X26	5-3/4"	360	1542.0	3413	27300.0	15'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-10-16	2000	10	16	W10X26	5-3/4"	360	1592.0	3413	27300.0	16'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-10-17	2000	10	17	W10X26	5-3/4"	360	1822.0	3413	27300.0	17'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-10-18	2000	10	18	W10X26	5-3/4"	360	1876.0	3413	27300.0	18'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-10-19	2000	10	19	W10X26	5-3/4"	360	1932.0	3413	27300.0	19'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-10-20	2000	10	20	W10X26	5-3/4"	360	1986.0	3413	27300.0	20'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-8	2000	11	8	W10X26	5-3/4"	360	1059.0	3772	30173.0	8'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-11-9	2000	11	9	W10X26	5-3/4"	360	1109.0	3772	30173.0	9'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-11-10	2000	11	10	W10X26	5-3/4"	360	1159.0	3772	30173.0	10'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-11-11	2000	11	11	W10X26	5-3/4"	360	1519.0	3772	30173.0	11'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-12	2000	11	12	W10X26	5-3/4"	360	1574.0	3772	30173.0	12'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-13	2000	11	13	W10X26	5-3/4"	360	1627.0	3772	30173.0	13'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-14	2000	11	14	W10X26	5-3/4"	360	1682.0	3772	30173.0	14'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-15	2000	11	15	W12X30	6-1/2"	360	1793.0	3802	30415.0	16'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-16	2000	11	16	W12X30	6-1/2"	360	1848.0	3802	30415.0	17'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-17	2000	11	17	W12X30	6-1/2"	360	1902.0	3802	30415.0	18'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-18	2000	11	18	W12X30	6-1/2"	360	1957.0	3802	30415.0	19'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-19	2000	11	19	W12X30	6-1/2"	360	2210.0	3802	30415.0	20'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-11-20	2000	11	20	W12X30	6-1/2"	360	2265.0	3802	30415.0	21'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-8	2000	12	8	W10X26	5-3/4"	360	1085.0	4134	33072.0	8'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-12-9	2000	12	9	W10X26	5-3/4"	360	1135.0	4134	33072.0	9'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-12-10	2000	12	10	W10X26	5-3/4"	360	1185.0	4134	33072.0	10'-10"	12"	15"	32"	36"	6	5.5' X 5.5' X 4'	4'-0 1/4"	5x3x3
351-2000-12-11	2000	12	11	W10X26	5-3/4"	360	1545.0	4134	33072.0	11'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-12-12	2000	12	12	W10X26	5-3/4"	360	1600.0	4134	33072.0	12'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-13	2000	12	13	W10X26	5-3/4"	360	1653.0	4134	33072.0	13'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-14	2000	12	14	W10X26	5-3/4"	360	1708.0	4134	33072.0	14'-10"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-15	2000	12	15	W12X30	6-1/2"	360	1823.0	4170	33360.0	16'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-16	2000	12	16	W12X30	6-1/2"	360	1878.0	4170	33360.0	17'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-17	2000	12	17	W12X30	6-1/2"	360	1932.0	4170	33360.0	18'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-18	2000	12	18	W12X30	6-1/2"	360	1987.0	4170	33360.0	19'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-19	2000	12	19	W12X30	6-1/2"	360	2240.0	4170	33360.0	20'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-12-20	2000	12	20	W12X30	6-1/2"	360	2295.0	4170	33360.0	21'-0"	14"	16"	32"	36"	6	5.5' X 5.5' X 4'	4'-6 1/4"	5x3x3
351-2000-13-8	2000	13	8	W12X30	6-1/2"	360	1518.0	4542	36335.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-9	2000	13	9	W12X30	6-1/2"	360	1548.0	4542	36335.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-10	2000	13	10	W12X30	6-1/2"	360	1578.0	4542	36335.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-11	2000	13	11	W12X30	6-1/2"	360	1658.0	4542	36335.0	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-12	2000	13	12	W12X30	6-1/2"	360	1688.0	4542	36335.0	13'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-13	2000	13	13	W16X45	7"	360	1969.0	4700	37602.5	14'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-14	2000	13	14	W16X45	7"	360	2014.0	4700	37602.5	15'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-15	2000	13	15	W16X45	7"	360	2079.0	4700	37602.5	16'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-16	2000	13	16	W16X45	7"	360	2124.0	4700	37602.5	17'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-13-17	2000	13	17	W16X45	7"	360	2749.0	1710	37602.5	18'-4"	16"	22"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-13-18	2000	13	18	W16X45	7"	360	2794.0	1710	37602.5	19'-4"	16"	22"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-13-19	2000	13	19	W16X45	7"	360	2875.0	1710	37602.5	20'-4"	16"	22"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-13-20	2000	13	20	W16X45	7"	360	2920.0	1710	37602.5	21'-4"	16"	22"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-14-8	2000	14	8	W12X30	6-1/2"	360	1548.0	4917	39340.0	9'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-9	2000	14	9	W12X30	6-1/2"	360	1578.0	4917	39340.0	10'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-10	2000	14	10	W12X30	6-1/2"	360	1608.0	4917	39340.0	11'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-11	2000	14	11	W12X30	6-1/2"	360	1688.0	4917	39340.0	12'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-12	2000	14	12	W12X30	6-1/2"	360	1718.0	4917	39340.0	13'-0"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-13	2000	14	13	W16X45	7"	360	2014.0	5101	40810.0	14'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-14	2000	14	14	W16X45	7"	360	2059.0	5101	40810.0	15'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-15	2000	14	15	W16X45	7"	360	2124.0	5101	40810.0	16'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-16	2000	14	16	W16X45	7"	360	2169.0	5101	40810.0	17'-4"	14"	16"	32"	36"	6	6' X 6' X 4'	4'-6 1/4"	5x3x3
351-2000-14-17	2000	14	17	W16X45	7"	360	2794.0	1855	40810.0	18'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-14-18	2000	14	18	W16X45	7"	360	2839.0	1855	40810.0	19'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-14-19	2000	14	19	W16X45	7"	360	2920.0	1855	40810.0	20'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-14-20	2000	14	20	W16X45	7"	360	2965.0	1855	40810.0	21'-4"	16"	19"	44"	48"	12	6' X 6' X 4'	5'-0 1/4"	6x3x3
351-2000-15-8	2000	15	8	W16X45	7"	360	1775.0	5508	44062.5	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-15-9	2000	15	9	W16X45	7"	360	1830.0	5508	44062.5	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-15-10	2000	15	10	W16X45	7"	360	1884.0	5508	44062.5	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-15-11	2000	15	11	W16X45	7"	360	1940.0	5508	44062.5	12'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-15-12	2000	15	12	W16X45	7"	360	1994.0	5508	44062.5	13'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-15-13	2000	15	13	W16X45	7"	360	2570.0	2003	44062.5	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-15-14	2000	15	14	W16X45	7"	360	2633.0	2003	44062.5	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-15-15	2000	15	15	W16X45	7"	360	2695.0	2003	44062.5	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-15-16	2000	15	16	W16X45	7"	360	2758.0	2003	44062.5	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-15-17	2000	15	17	W16X45	7"	360	3146.0	2003	44062.5	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-15-18	2000	15	18	W16X45	7"	360	3217.0	2003	44062.5	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-15-19	2000	15	19	W16X45	7"	360	3289.0	2003	44062.5	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-15-20	2000	15	20	W16X45	7"	360	3360.0	2003	44062.5	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-16-8	2000	16	8	W16X45	7"	360	1820.0	5920	47360.0	9'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-16-9	2000	16	9	W16X45	7"	360	1875.0	5920	47360.0	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-16-10	2000	16	10	W16X45	7"	360	1929.0	5920	47360.0	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-16-11	2000	16	11	W16X45	7"	360	1985.0	5920	47360.0	12'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-16-12	2000	16	12	W16X45	7"	360	2039.0	5920	47360.0	13'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-16-13	2000	16	13	W16X45	7"	360	2615.0	2153	47360.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-16-14	2000	16	14	W16X45	7"	360	2678.0	2153	47360.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-16-15	2000	16	15	W16X45	7"	360	2740.0	2153	47360.0	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-16-16	2000	16	16	W16X45	7"	360	2803.0	2153	47360.0	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-16-17	2000	16	17	W16X45	7"	360	3191.0	2153	47360.0	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-16-18	2000	16	18	W16X45	7"	360	3262.0	2153	47360.0	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-16-19	2000	16	19	W16X45	7"	360	3334.0	2153	47360.0	20'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-16-20	2000	16	20	W16X45	7"	360	3405.0	2153	47360.0	21'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-17-8	2000	17	8	W16X45	7"	360	1866.0	6338	50702.5	19'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-17-9	2000	17	9	W16X45	7"	360	1920.0	6338	50702.5	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-17-10	2000	17	10	W16X45	7"	360	1974.0	6338	50702.5	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-17-11	2000	17	11	W16X45	7"	360	2534.0	2305	50702.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-17-12	2000	17	12	W16X45	7"	360	2597.0	2305	50702.5	13'-4"	16"	19"	42"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-17-13	2000	17	13	W16X45	7"	360	2660.0	2305	50702.5	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-17-14	2000	17	14	W16X45	7"	360	2723.0	2305	50702.5	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-17-15	2000	17	15	W18X55	7-1/2"	360	2988.0	2371	52147.5	16'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-17-16	2000	17	16	W18X55	7-1/2"	360	3051.0	2371	52147.5	17'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-17-17	2000	17	17	W16X45	7"	360	3236.0	2305	50702.5	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-17-18	2000	17	18	W16X45	7"	360	3307.0	2305	50702.5	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-17-19	2000	17	19	W18X55	7-1/2"	360	3564.0	2371	52147.5	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-17-20	2000	17	20	W18X55	7-1/2"	360	3635.0	2371	52147.5	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-18-8	2000	18	8	W16X45	7"	360	1911.0	6761	54090.0	19'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-18-9	2000	18	9	W16X45	7"	360	1965.0	6761	54090.0	10'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-18-10	2000	18	10	W16X45	7"	360	2019.0	6761	54090.0	11'-4"	14"	16"	32"	36"	6	7' X 7' X 4'	4'-6 1/4"	5x3x3
351-2000-18-11	2000	18	11	W16X45	7"	360	2579.0	2459	54090.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-12	2000	18	12	W16X45	7"	360	2642.0	2459	54090.0	13'-4"	16"	19"	42"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-13	2000	18	13	W16X45	7"	360	2705.0	2459	54090.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-14	2000	18	14	W16X45	7"	360	2768.0	2459	54090.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-15	2000	18	15	W18X55	7-1/2"	360	3043.0	2533	55710.0	16'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-16	2000	18	16	W18X55	7-1/2"	360	3106.0	2533	55710.0	17'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-18-17	2000	18	17	W16X45	7"	360	3281.0	2459	54090.0	18'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-18-18	2000	18	18	W16X45	7"	360	3352.0	2459	54090.0	19'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-18-19	2000	18	19	W18X55	7-1/2"	360	3619.0	2533	55710.0	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-18-20	2000	18	20	W18X55	7-1/2"	360	3690.0	2533	55710.0	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-19-8	2000	19	8	W16X45	7"	360	2435.0	2615	57522.5	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-19-9	2000	19	9	W16X45	7"	360	2498.0	2615	57522.5	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-10	2000	19	10	W16X45	7"	360	2561.0	2615	57522.5	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-11	2000	19	11	W16X45	7"	360	2624.0	2615	57522.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-12	2000	19	12	W16X45	7"	360	2687.0	2615	57522.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-13	2000	19	13	W18X55	7-1/2"	360	2972.0	2697	59327.5	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-14	2000	19	14	W18X55	7-1/2"	360	3035.0	2697	59327.5	15'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-15	2000	19	15	W18X55	7-1/2"	360	3098.0	2697	59327.5	16'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-16	2000	19	16	W18X55	7-1/2"	360	3161.0	2697	59327.5	17'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-19-17	2000	19	17	W18X55	7-1/2"	360	3532.0	2697	59327.5	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-19-18	2000	19	18	W18X55	7-1/2"	360	3603.0	2697	59327.5	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-19-19	2000	19	19	W18X55	7-1/2"	360	3674.0	2697	59327.5	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-19-20	2000	19	20	W18X55	7-1/2"	360	3745.0	2697	59327.5	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-20-8	2000	20	8	W16X45	7"	360	2480.0	2773	61000.0	9'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-9	2000	20	9	W16X45	7"	360	2543.0	2773	61000.0	10'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-10	2000	20	10	W16X45	7"	360	2606.0	2773	61000.0	11'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-11	2000	20	11	W16X45	7"	360	2669.0	2773	61000.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-12	2000	20	12	W16X45	7"	360	2732.0	2773	61000.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-13	2000	20	13	W18X55	7-1/2"	360	3027.0	2864	63000.0	14'-6"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-2000-20-14	2000	20	14	W18X55	7-1/2"	360	3090.0	2864	63000.0	15'-6"	16"	19"	44"	48"	12	8' X 8' X 4'	5'-0 1/4"	6x3x3
351-2000-20-15	2000	20	15	W18X55	7-1/2"	360	3153.0	2864	63000.0	16'-6"	16"	19"	44"	48"	12	8' X 8' X 4'	5'-0 1/4"	6x3x3
351-2000-20-16	2000	20	16	W18X55	7-1/2"	360	3216.0	2864	63000.0	17'-6"	16"	19"	44"	48"	12	8' X 8' X 4'	5'-0 1/4"	6x3x3
351-2000-20-17	2000	20	17	W18X55	7-1/2"	360	3587.0	2864	63000.0	18'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-2000-20-18	2000	20	18	W18X55	7-1/2"	360	3658.0	2864	63000.0	19'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-20-19	2000	20	19	W18X55	7-1/2"	360	3729.0	2864	63000.0	20'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-2000-20-20	2000	20	20	W18X55	7-1/2"	360	3800.0	2864	63000.0	21'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5