

## Pallet Stackers - 24" Load Center

Presto Pallet Stackers are ideal for use with pallet racks. Choose from over 25 models with capacities to 2,700 lbs., lifting heights to 12 feet and a wide variety of available options.

### Features

- Fixed or adjustable base
- Fixed and telescopic masts
- Adjustable solid steel forks
  - 1-1/2" thick x 3" wide x 36" long (1500 & 2000 lb. capacities)
  - 1-1/2" thick x 4" wide x 36" long (2700 lb. capacities)
- Lifting speed: 4"/sec. 1500 & 2000 lb. - 2" per sec. 2700 lb.
- Hand-operated floor lock
- Heavy-duty 12V battery
- Custom microprocessor charger
- Fifth wheel for greater mobility
- Dual leaf-type chains with 8250 lb. yield point
- Dual roller chain for 2700 lb. lift
- Forks adjust from 6-1/2" to 30" O.D.
- 14" high fork backs
- Turning radius with 48" load:
  - 106" aisle with 42" I.D. base
  - 110" aisle with 50" I.D. base
  - 112" aisle with adjustable base @ 50" I.D.



Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H x W x L	Base Legs I.D. / O.D.	Wheel Dia. Front/Rear	Shipping Weight
<b>PS Series - 42" I.D. Straddle - 24" Load Center</b>							
PS262	2000 lbs	62"	2-1/2"	82 x 48 x 70"	42" / 48"	5" / 4"	875 lbs
PS274	2000 lbs	72"	2-1/2"	94 x 48 x 70"	42" / 48"	5" / 4"	925 lbs
PS2762	2700 lbs	60"	2-1/2"	84 x 48 x 70"	42" / 48"	5" / 4"	1000 lbs
PS2774	2700 lbs	72"	2-1/2"	96 x 48 x 70"	42" / 48"	5" / 4"	1045 lbs
<b>PS50 Series - 50" I.D. Straddle - 24" Load Center</b>							
PS262-50	2000 lbs	62"	2-1/2"	82 x 56 x 70"	50" / 56"	5" / 4"	900 lbs
PS274-50	2000 lbs	74"	2-1/2"	94 x 56 x 70"	50" / 56"	5" / 4"	975 lbs
PS2762-50	2700 lbs	60"	2-1/2"	84 x 56 x 70"	50" / 56"	5" / 4"	1025 lbs
PS2774-50	2700 lbs	72"	2-1/2"	96 x 56 x 70"	50" / 56"	5" / 4"	1070 lbs
<b>PSA Series - Adjustable Base - Straddle (35" I.D. to 50" I.D.) - 24" Load Center</b>							
PSA262	2000 lbs	62"	2-1/2"	82 x 41-56 x 72"	35-50" / 41-56"	5" / 5"	1000 lbs
PSA274	2000 lbs	74"	2-1/2"	94 x 41-56 x 72"	35-50" / 41-56"	5" / 5"	1045 lbs
PSA2762	2700 lbs	60"	2-1/2"	84 x 41-56 x 72"	35-50" / 41-56"	5" / 5"	1145 lbs
PSA2774	2700 lbs	72"	2-1/2"	96 x 41-56 x 72"	35-50" / 41-56"	5" / 5"	1175 lbs
<b>PST Series - 42" I.D. Straddle - Telescoping Mast - 24" Load Center</b>							
PST294	2000 lbs	94"	2-1/2"	119/73 x 48 x 71"	42-48"	5" / 4"	1000 lbs
PST2107	2000 lbs	107"	2-1/2"	133/81 x 48 x 71"	42-48"	5" / 4"	1050 lbs
PST2127	2000 lbs	127"	2-1/2"	155/93 x 48 x 71"	42-48"	5" / 4"	1100 lbs
PST2144	2000 lbs	144"	2-1/2"	169/99 x 48 x 71"	42-48"	5" / 4"	1150 lbs
PST2794	2700 lbs	94"	2-1/2"	119/75 x 48 x 71"	42-48"	5" / 4"	1190 lbs
PST27107	2700 lbs	107"	2-1/2"	133/81 x 48 x 71"	42-48"	5" / 4"	1240 lbs
PST27127	2700 lbs	127"	2-1/2"	156/94 x 48 x 71"	42-48"	5" / 4"	1290 lbs
<b>PST 50 Series - 50" I.D. Straddle - Telescoping Mast - 24" Load Center</b>							
PST294-50	2000 lbs	94"	2-1/2"	119/73 x 56 x 71"	50-56"	5" / 4"	1010 lbs
PST2107-50	2000 lbs	107"	2-1/2"	133/81 x 56 x 71"	50-56"	5" / 4"	1060 lbs
PST2127-50	2000 lbs	127"	2-1/2"	155/93 x 56 x 71"	50-56"	5" / 4"	1110 lbs
PST2144-50	2000 lbs	144"	2-1/2"	169/99 x 56 x 71"	50-56"	5" / 4"	1170 lbs
PST2794-50	2700 lbs	94"	2-1/2"	119/75 x 56 x 71"	50-56"	5" / 4"	1200 lbs
PST27107-50	2700 lbs	107"	2-1/2"	133/81 x 56 x 71"	50-56"	5" / 4"	1250 lbs
PST27127-50	2700 lbs	127"	2-1/2"	156/94 x 56 x 71"	50-56"	5" / 4"	1300 lbs
<b>PSTA Series - Adjustable Base - Straddle (35" I.D. to 50" I.D.) - 24" Load Center</b>							
PSTA294	2000 lbs	94"	2-1/2"	119/73 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1150 lbs
PSTA2107	2000 lbs	107"	2-1/2"	133/80 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1200 lbs
PSTA2127	2000 lbs	127"	2-1/2"	154/92 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1250 lbs
PSTA2794	2700 lbs	94"	2-1/2"	120/75 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1400 lbs
PSTA27107	2700 lbs	107"	2-1/2"	133/81 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1450 lbs
PSTA27127	2700 lbs	127"	2-1/2"	156/93 x 41-56 x 73"	35-50" / 41-56"	5" / 5"	1500 lbs

Units over 93" in height will be shipped in the horizontal position.