



Heavy Duty Freestanding Jib Crane - 351 Series - From 6000 To 10000 lbs Capacity

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-8-8	6000	8	8	W12X35	6 1/2"	360	2028.0	2874	63232.0	9'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-9	6000	8	9	W12X35	6 1/2"	360	2065.0	2874	63232.0	10'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-10	6000	8	10	W12X35	6 1/2"	360	2128.0	2874	63232.0	11'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-11	6000	8	11	W16X45	7"	360	2152.0	2902	63840.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-12	6000	8	12	W16X45	7"	360	2215.0	2902	63840.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-13	6000	8	13	W16X45	7"	360	2277.0	2902	63840.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-14	6000	8	14	W16X45	7"	360	2340.0	2902	63840.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-15	6000	8	15	W16X45	7"	360	2402.0	2902	63840.0	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-16	6000	8	16	W16X45	7"	360	2465.0	2902	63840.0	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-17	6000	8	17	W16X45	7"	360	2872.0	2902	63840.0	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-18	6000	8	18	W16X45	7"	360	2935.0	2902	63840.0	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-19	6000	8	19	W16X45	7"	360	3013.0	2902	63840.0	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-8-20	6000	8	20	W16X45	7"	360	3075.0	2902	63840.0	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-8	6000	9	8	W12X35	6 1/2"	360	2054.0	3239	71253.0	9'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-9	6000	9	9	W12X35	6 1/2"	360	2091.0	3239	71253.0	10'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-10	6000	9	10	W12X35	6 1/2"	360	2154.0	3239	71253.0	11'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-11	6000	9	11	W16X45	7"	360	2197.0	3274	72022.5	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-12	6000	9	12	W16X45	7"	360	2260.0	3274	72022.5	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-13	6000	9	13	W16X45	7"	360	2322.0	3274	72022.5	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-14	6000	9	14	W16X45	7"	360	2385.0	3274	72022.5	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-9-15	6000	9	15	W16X45	7"	360	2447.0	3274	72022.5	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-16	6000	9	16	W16X45	7"	360	2510.0	3274	72022.5	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-17	6000	9	17	W16X45	7"	360	2917.0	3274	72022.5	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-18	6000	9	18	W16X45	7"	360	2980.0	3274	72022.5	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-19	6000	9	19	W16X45	7"	360	3058.0	3274	72022.5	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-9-20	6000	9	20	W16X45	7"	360	3120.0	3274	72022.5	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-8	6000	10	8	W12X35	6 1/2"	360	2054.0	3605	79300.0	9'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-9	6000	10	9	W12X35	6 1/2"	360	2117.0	3605	79300.0	10'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-10	6000	10	10	W12X35	6 1/2"	360	2180.0	3605	79300.0	11'-10"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-11	6000	10	11	W16X45	7"	360	2242.0	3648	80250.0	12'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-12	6000	10	12	W16X45	7"	360	2305.0	3648	80250.0	13'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-13	6000	10	13	W16X45	7"	360	2367.0	3648	80250.0	14'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-14	6000	10	14	W16X45	7"	360	2430.0	3648	80250.0	15'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-15	6000	10	15	W16X45	7"	360	2492.0	3648	80250.0	16'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-16	6000	10	16	W16X45	7"	360	2555.0	3648	80250.0	17'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-17	6000	10	17	W16X45	7"	360	2962.0	3648	80250.0	18'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-18	6000	10	18	W16X45	7"	360	3025.0	3648	80250.0	19'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-19	6000	10	19	W16X45	7"	360	3103.0	3648	80250.0	20'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-10-20	6000	10	20	W16X45	7"	360	3165.0	3648	80250.0	21'-4"	16"	19"	44"	48"	12	7' X 7' X 4'	5'-0 1/4"	6x3x3
351-6000-11-8	6000	11	8	W16X45	7"	360	2363.0	4024	88522.5	9'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-9	6000	11	9	W16X45	7"	360	2434.0	4024	88522.5	10'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-10	6000	11	10	W16X45	7"	360	2505.0	4024	88522.5	11'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-11-11	6000	11	11	W16X45	7"	360	2574.0	4024	88522.5	12'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-12	6000	11	12	W16X45	7"	360	2645.0	4024	88522.5	13'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-13	6000	11	13	W16X45	7"	360	2714.0	4024	88522.5	14'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-14	6000	11	14	W16X45	7"	360	2785.0	4024	88522.5	15'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-15	6000	11	15	W18X55	7 1/2"	360	2979.0	4051	89127.5	16'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-16	6000	11	16	W18X55	7 1/2"	360	3050.0	4051	89127.5	17'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-17	6000	11	17	W18X55	7 1/2"	360	3124.0	4051	89127.5	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-18	6000	11	18	W18X55	7 1/2"	360	3195.0	4051	89127.5	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-19	6000	11	19	W18X55	7 1/2"	360	3264.0	4051	89127.5	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-11-20	6000	11	20	W18X55	7 1/2"	360	3335.0	4051	89127.5	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-8	6000	12	8	W16X45	7"	360	2408.0	4402	96840.0	9'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-9	6000	12	9	W16X45	7"	360	2479.0	4402	96840.0	10'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-10	6000	12	10	W16X45	7"	360	2550.0	4402	96840.0	11'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-11	6000	12	11	W16X45	7"	360	2619.0	4402	96840.0	12'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-12	6000	12	12	W16X45	7"	360	2690.0	4402	96840.0	13'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-13	6000	12	13	W16X45	7"	360	2759.0	4402	96840.0	14'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-14	6000	12	14	W16X45	7"	360	2830.0	4402	96840.0	15'-4"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-15	6000	12	15	W18X55	7 1/2"	360	3034.0	4435	97560.0	16'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-16	6000	12	16	W18X55	7 1/2"	360	3105.0	4435	97560.0	17'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-17	6000	12	17	W18X55	7 1/2"	360	3179.0	4435	97560.0	18'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-18	6000	12	18	W18X55	7 1/2"	360	3250.0	4435	97560.0	19'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-12-19	6000	12	19	W18X55	7 1/2"	360	3319.0	4435	97560.0	20'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-12-20	6000	12	20	W18X55	7 1/2"	360	3390.0	4435	97560.0	21'-6"	18"	22"	44"	48"	12	7' X 7' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-8	6000	13	8	W18X55	7-1/2"	360	2598.0	4820	106047.5	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-9	6000	13	9	W18X55	7-1/2"	360	2669.0	4820	106047.5	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-10	6000	13	10	W18X55	7-1/2"	360	2740.0	4820	106047.5	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-11	6000	13	11	W18X55	7-1/2"	360	2809.0	4820	106047.5	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-12	6000	13	12	W18X55	7-1/2"	360	2880.0	4820	106047.5	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-13-13	6000	13	13	W18X55	7-1/2"	360	3591.0	4419	106047.5	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-14	6000	13	14	W18X55	7-1/2"	360	3670.0	4419	106047.5	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-15	6000	13	15	W18X55	7-1/2"	360	3751.0	4419	106047.5	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-16	6000	13	16	W18X55	7-1/2"	360	3830.0	4419	106047.5	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-17	6000	13	17	W18X55	7-1/2"	360	3906.0	4419	106047.5	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-18	6000	13	18	W18X55	7-1/2"	360	3985.0	4419	106047.5	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-19	6000	13	19	W21X62	8 1/4"	360	4184.0	4444	106639.0	20'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-13-20	6000	13	20	W21X62	8 1/4"	360	4263.0	4444	106639.0	21'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-8	6000	14	8	W18X55	7-1/2"	360	2653.0	5209	114590.0	9'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-14-9	6000	14	9	W18X55	7-1/2"	360	2724.0	5209	114590.0	10'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-14-10	6000	14	10	W18X55	7-1/2"	360	2795.0	5209	114590.0	11'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-14-11	6000	14	11	W18X55	7-1/2"	360	2864.0	5209	114590.0	12'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-14-12	6000	14	12	W18X55	7-1/2"	360	2935.0	5209	114590.0	13'-6"	18"	22"	44"	48"	12	8' X 8' X 4'	5'-6 1/4"	6x3.5x3.5
351-6000-14-13	6000	14	13	W18X55	7-1/2"	360	3646.0	4775	114590.0	14'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-14	6000	14	14	W18X55	7-1/2"	360	3725.0	4775	114590.0	15'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-15	6000	14	15	W18X55	7-1/2"	360	3806.0	4775	114590.0	16'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-14-16	6000	14	16	W18X55	7-1/2"	360	3885.0	4775	114590.0	17'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-17	6000	14	17	W18X55	7-1/2"	360	3961.0	4775	114590.0	18'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-18	6000	14	18	W18X55	7-1/2"	360	4040.0	4775	114590.0	19'-6"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-19	6000	14	19	W21X62	8 1/4"	360	4246.0	4804	115276.0	20'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-14-20	6000	14	20	W21X62	8 1/4"	360	4325.0	4804	115276.0	21'-9"	20"	28"	48"	54"	12	8' X 8' X 4'	6'-6 1/4"	7x4x4
351-6000-15-8	6000	15	8	W18X55	7 1/2"	360	3312.0	5133	123187.5	9'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-9	6000	15	9	W18X55	7 1/2"	360	3391.0	5133	123187.5	10'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-10	6000	15	10	W18X55	7 1/2"	360	3470.0	5133	123187.5	11'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-11	6000	15	11	W18X55	7 1/2"	360	3546.0	5133	123187.5	12'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-12	6000	15	12	W18X55	7 1/2"	360	3625.0	5133	123187.5	13'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-13	6000	15	13	W21X62	8 1/4"	360	3839.0	5166	123975.0	14'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-14	6000	15	14	W21X62	8 1/4"	360	3918.0	5166	123975.0	15'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-15	6000	15	15	W21X62	8 1/4"	360	3994.0	5166	123975.0	16'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-16	6000	15	16	W21X62	8 1/4"	360	4073.0	5166	123975.0	17'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-17	6000	15	17	W21X62	8 1/4"	360	4653.0	5166	123975.0	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-18	6000	15	18	W21X62	8 1/4"	360	4748.0	5166	123975.0	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-19	6000	15	19	W21X62	8 1/4"	360	4843.0	5166	123975.0	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-15-20	6000	15	20	W21X62	8 1/4"	360	4938.0	5166	123975.0	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-8	6000	16	8	W18X55	7 1/2"	360	3367.0	5494	131840.0	9'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-9	6000	16	9	W18X55	7 1/2"	360	3446.0	5494	131840.0	10'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-10	6000	16	10	W18X55	7 1/2"	360	3525.0	5494	131840.0	11'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-11	6000	16	11	W18X55	7 1/2"	360	3601.0	5494	131840.0	12'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-16-12	6000	16	12	W18X55	7 1/2"	360	3680.0	5494	131840.0	13'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-13	6000	16	13	W21X62	8 1/4"	360	3901.0	5531	132736.0	14'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-14	6000	16	14	W21X62	8 1/4"	360	3980.0	5531	132736.0	15'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-15	6000	16	15	W21X62	8 1/4"	360	4056.0	5531	132736.0	16'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-16	6000	16	16	W21X62	8 1/4"	360	4135.0	5531	132736.0	17'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-17	6000	16	17	W21X62	8 1/4"	360	4715.0	5531	132736.0	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-18	6000	16	18	W21X62	8 1/4"	360	4810.0	5531	132736.0	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-19	6000	16	19	W21X62	8 1/4"	360	4905.0	5531	132736.0	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-16-20	6000	16	20	W21X62	8 1/4"	360	5000.0	5531	132736.0	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-8	6000	17	8	W21X62	8-1/4"	360	3565.0	5899	141559.0	9'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-9	6000	17	9	W21X62	8-1/4"	360	3644.0	5899	141559.0	10'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-10	6000	17	10	W21X62	8-1/4"	360	3723.0	5899	141559.0	11'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-11	6000	17	11	W21X62	8-1/4"	360	4073.0	5899	141559.0	12'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-12	6000	17	12	W21X62	8-1/4"	360	4178.0	5899	141559.0	13'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-13	6000	17	13	W21X62	8-1/4"	360	4398.0	5899	141559.0	14'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-14	6000	17	14	W21X62	8-1/4"	360	4493.0	5899	141559.0	15'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-15	6000	17	15	W21X62	8-1/4"	360	4588.0	5899	141559.0	16'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-16	6000	17	16	W21X62	8-1/4"	360	4683.0	5899	141559.0	17'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-17	6000	17	17	W21X62	8-1/4"	360	5298.0	5899	141559.0	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-18	6000	17	18	W21X62	8-1/4"	360	5423.0	5899	141559.0	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-19	6000	17	19	W21X62	8-1/4"	360	5548.0	5899	141559.0	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-17-20	6000	17	20	W21X62	8-1/4"	360	5673.0	5899	141559.0	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-18-8	6000	18	8	W21X62	8-1/4"	360	3627.0	6269	150444.0	9'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-9	6000	18	9	W21X62	8-1/4"	360	3706.0	6269	150444.0	10'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-10	6000	18	10	W21X62	8-1/4"	360	3785.0	6269	150444.0	11'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-11	6000	18	11	W21X62	8-1/4"	360	4135.0	6269	150444.0	12'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-12	6000	18	12	W21X62	8-1/4"	360	4240.0	6269	150444.0	13'-9"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-13	6000	18	13	W21X62	8-1/4"	360	4460.0	6269	150444.0	14'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-14	6000	18	14	W21X62	8-1/4"	360	4555.0	6269	150444.0	15'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-15	6000	18	15	W21X62	8-1/4"	360	4650.0	6269	150444.0	16'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-16	6000	18	16	W21X62	8-1/4"	360	4745.0	6269	150444.0	17'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-17	6000	18	17	W21X62	8-1/4"	360	5360.0	6269	150444.0	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-18	6000	18	18	W21X62	8-1/4"	360	5485.0	6269	150444.0	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-19	6000	18	19	W21X62	8-1/4"	360	5610.0	6269	150444.0	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-18-20	6000	18	20	W21X62	8-1/4"	360	5735.0	6269	150444.0	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-8	6000	19	8	W24X76	9	360	4344.0	6747	161918.0	10'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-9	6000	19	9	W24X76	9	360	4439.0	6747	161918.0	11'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-10	6000	19	10	W24X76	9	360	4534.0	6747	161918.0	12'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-11	6000	19	11	W24X76	9	360	4629.0	6747	161918.0	13'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-12	6000	19	12	W24X76	9	360	4724.0	6747	161918.0	14'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-13	6000	19	13	W24X76	9	360	4819.0	6747	161918.0	15'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-14	6000	19	14	W24X76	9	360	4914.0	6747	161918.0	16'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-15	6000	19	15	W21X83	8 3/8"	360	5612.0	6800	163181.5	16'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-16	6000	19	16	W21X83	8 3/8"	360	5737.0	6800	163181.5	17'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-6000-19-17	6000	19	17	W21X83	8 3/8"	360	5862.0	6800	163181.5	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-18	6000	19	18	W21X83	8 3/8"	360	5987.0	6800	163181.5	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-19	6000	19	19	W21X83	8 3/8"	360	6112.0	6800	163181.5	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-19-20	6000	19	20	W21X83	8 3/8"	360	6237.0	6800	163181.5	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-8	6000	20	8	W24X76	9	360	4420.0	7134	171200.0	10'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-9	6000	20	9	W24X76	9	360	4515.0	7134	171200.0	11'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-10	6000	20	10	W24X76	9	360	4610.0	7134	171200.0	12'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-11	6000	20	11	W24X76	9	360	4705.0	7134	171200.0	13'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-12	6000	20	12	W24X76	9	360	4800.0	7134	171200.0	14'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-13	6000	20	13	W24X76	9	360	4895.0	7134	171200.0	15'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-14	6000	20	14	W24X76	9	360	4990.0	7134	171200.0	16'-0"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-15	6000	20	15	W21X83	8 3/8"	360	5695.0	7192	172600.0	16'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-16	6000	20	16	W21X83	8 3/8"	360	5820.0	7192	172600.0	17'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-17	6000	20	17	W21X83	8 3/8"	360	5945.0	7192	172600.0	18'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-18	6000	20	18	W21X83	8 3/8"	360	6070.0	7192	172600.0	19'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-19	6000	20	19	W21X83	8 3/8"	360	6195.0	7192	172600.0	20'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-6000-20-20	6000	20	20	W21X83	8 3/8"	360	6320.0	7192	172600.0	21'-9"	24"	29"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-8	10000	8	8	W18X55	7 1/2"	360	2927.0	4407	105760.0	9'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-9	10000	8	9	W18X55	7 1/2"	360	3006.0	4407	105760.0	10'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-10	10000	8	10	W18X55	7 1/2"	360	3085.0	4407	105760.0	11'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-11	10000	8	11	W18X55	7 1/2"	360	3166.0	4407	105760.0	12'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-12	10000	8	12	W18X55	7 1/2"	360	3245.0	4407	105760.0	13'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-8-13	10000	8	13	W18X55	7 1/2"	360	3321.0	4407	105760.0	14'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-14	10000	8	14	W18X55	7 1/2"	360	3400.0	4407	105760.0	15'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-15	10000	8	15	W18X55	7 1/2"	360	3856.0	4407	105760.0	16'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-16	10000	8	16	W18X55	7 1/2"	360	3960.0	4407	105760.0	17'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-17	10000	8	17	W18X55	7 1/2"	360	4060.0	4407	105760.0	18'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-18	10000	8	18	W18X55	7 1/2"	360	4165.0	4407	105760.0	19'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-19	10000	8	19	W18X55	7 1/2"	360	4271.0	4407	105760.0	20'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-8-20	10000	8	20	W18X55	7 1/2"	360	4375.0	4407	105760.0	21'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-8	10000	9	8	W18X55	7 1/2"	360	2982.0	4968	119227.5	9'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-9	10000	9	9	W18X55	7 1/2"	360	3061.0	4968	119227.5	10'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-10	10000	9	10	W18X55	7 1/2"	360	3140.0	4968	119227.5	11'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-11	10000	9	11	W18X55	7 1/2"	360	3221.0	4968	119227.5	12'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-12	10000	9	12	W18X55	7 1/2"	360	3300.0	4968	119227.5	13'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-13	10000	9	13	W18X55	7 1/2"	360	3376.0	4968	119227.5	14'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-14	10000	9	14	W18X55	7 1/2"	360	3455.0	4968	119227.5	15'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-15	10000	9	15	W18X55	7 1/2"	360	3911.0	4968	119227.5	16'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-16	10000	9	16	W18X55	7 1/2"	360	4015.0	4968	119227.5	17'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-17	10000	9	17	W18X55	7 1/2"	360	4115.0	4968	119227.5	18'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-18	10000	9	18	W18X55	7 1/2"	360	4220.0	4968	119227.5	19'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-19	10000	9	19	W18X55	7 1/2"	360	4326.0	4968	119227.5	20'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-9-20	10000	9	20	W18X55	7 1/2"	360	4430.0	4968	119227.5	21'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-8	10000	10	8	W18X55	7 1/2"	360	3037.0	5532	132750.0	9'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-10-9	10000	10	9	W18X55	7 1/2"	360	3116.0	5532	132750.0	10'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-10	10000	10	10	W18X55	7 1/2"	360	3195.0	5532	132750.0	11'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-11	10000	10	11	W18X55	7 1/2"	360	3276.0	5532	132750.0	12'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-12	10000	10	12	W18X55	7 1/2"	360	3355.0	5532	132750.0	13'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-13	10000	10	13	W18X55	7 1/2"	360	3431.0	5532	132750.0	14'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-14	10000	10	14	W18X55	7 1/2"	360	3510.0	5532	132750.0	15'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-15	10000	10	15	W18X55	7 1/2"	360	3966.0	5532	132750.0	16'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-16	10000	10	16	W18X55	7 1/2"	360	4070.0	5532	132750.0	17'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-17	10000	10	17	W18X55	7 1/2"	360	4171.0	5532	132750.0	18'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-18	10000	10	18	W18X55	7 1/2"	360	4275.0	5532	132750.0	19'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-19	10000	10	19	W18X55	7 1/2"	360	4381.0	5532	132750.0	20'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-10-20	10000	10	20	W18X55	7 1/2"	360	4485.0	5532	132750.0	21'-6"	20"	28"	48"	54"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-8	10000	11	8	W21X68	8 1/4"	360	3632.0	5449	147114.0	9'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-9	10000	11	9	W21X68	8 1/4"	360	3727.0	5449	147114.0	10'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-10	10000	11	10	W21X68	8 1/4"	360	3822.0	5449	147114.0	11'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-11	10000	11	11	W21X68	8 1/4"	360	3917.0	5449	147114.0	12'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-12	10000	11	12	W21X68	8 1/4"	360	4012.0	5449	147114.0	13'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-13	10000	11	13	W21X68	8 1/4"	360	4107.0	5449	147114.0	14'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-14	10000	11	14	W21X68	8 1/4"	360	4202.0	5449	147114.0	15'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-15	10000	11	15	W21X68	8 1/4"	360	4747.0	5449	147114.0	16'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-16	10000	11	16	W21X68	8 1/4"	360	4872.0	5449	147114.0	17'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-17	10000	11	17	W21X68	8 1/4"	360	5002.0	5449	147114.0	18'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-11-18	10000	11	18	W21X68	8 1/4"	360	5127.0	5449	147114.0	19'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-19	10000	11	19	W21X68	8 1/4"	360	5252.0	5449	147114.0	20'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-11-20	10000	11	20	W21X68	8 1/4"	360	5377.0	5449	147114.0	21'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-8	10000	12	8	W21X68	8 1/4"	360	3700.0	5960	160896.0	9'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-9	10000	12	9	W21X68	8 1/4"	360	3795.0	5960	160896.0	10'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-10	10000	12	10	W21X68	8 1/4"	360	3890.0	5960	160896.0	11'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-11	10000	12	11	W21X68	8 1/4"	360	3985.0	5960	160896.0	12'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-12	10000	12	12	W21X68	8 1/4"	360	4080.0	5960	160896.0	13'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-13	10000	12	13	W21X68	8 1/4"	360	4175.0	5960	160896.0	14'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-14	10000	12	14	W21X68	8 1/4"	360	4270.0	5960	160896.0	15'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-15	10000	12	15	W21X68	8 1/4"	360	4815.0	5960	160896.0	16'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-16	10000	12	16	W21X68	8 1/4"	360	4940.0	5960	160896.0	17'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-17	10000	12	17	W21X68	8 1/4"	360	5070.0	5960	160896.0	18'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-18	10000	12	18	W21X68	8 1/4"	360	5195.0	5960	160896.0	19'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-19	10000	12	19	W21X68	8 1/4"	360	5320.0	5960	160896.0	20'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-12-20	10000	12	20	W21X68	8 1/4"	360	5445.0	5960	160896.0	21'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-8	10000	13	8	W21X68	8 1/4"	360	4007.0	6473	174746.0	9'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-9	10000	13	9	W21X68	8 1/4"	360	4132.0	6473	174746.0	10'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-10	10000	13	10	W21X68	8 1/4"	360	4257.0	6473	174746.0	11'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-11	10000	13	11	W21X68	8 1/4"	360	4382.0	6473	174746.0	12'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-12	10000	13	12	W21X68	8 1/4"	360	4507.0	6473	174746.0	13'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-13	10000	13	13	W21X68	8 1/4"	360	4632.0	6473	174746.0	14'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-13-14	10000	13	14	W21X68	8 1/4"	360	4757.0	6473	174746.0	15'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-15	10000	13	15	W21X68	8 1/4"	360	4887.0	6473	174746.0	16'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-16	10000	13	16	W21X68	8 1/4"	360	5012.0	6473	174746.0	17'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-17	10000	13	17	W21X68	8 1/4"	360	5137.0	6473	174746.0	18'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-18	10000	13	18	W21X68	8 1/4"	360	5262.0	6473	174746.0	19'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-19	10000	13	19	W21X68	8 1/4"	360	5387.0	6473	174746.0	20'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-13-20	10000	13	20	W21X68	8 1/4"	360	5512.0	6473	174746.0	21'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-8	10000	14	8	W21X68	8 1/4"	360	4075.0	6988	188664.0	9'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-9	10000	14	9	W21X68	8 1/4"	360	4200.0	6988	188664.0	10'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-10	10000	14	10	W21X68	8 1/4"	360	4325.0	6988	188664.0	11'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-11	10000	14	11	W21X68	8 1/4"	360	4450.0	6988	188664.0	12'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-12	10000	14	12	W21X68	8 1/4"	360	4575.0	6988	188664.0	13'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-13	10000	14	13	W21X68	8 1/4"	360	4700.0	6988	188664.0	14'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-14	10000	14	14	W21X68	8 1/4"	360	4825.0	6988	188664.0	15'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-15	10000	14	15	W21X68	8 1/4"	360	4955.0	6988	188664.0	16'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-16	10000	14	16	W21X68	8 1/4"	360	5080.0	6988	188664.0	17'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-17	10000	14	17	W21X68	8 1/4"	360	5205.0	6988	188664.0	18'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-18	10000	14	18	W21X68	8 1/4"	360	5330.0	6988	188664.0	19'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-19	10000	14	19	W21X68	8 1/4"	360	5455.0	6988	188664.0	20'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-14-20	10000	14	20	W21X68	8 1/4"	360	5580.0	6988	188664.0	21'-9"	24"	29"	54"	60"	12	9' X 9' X 4'	6'-6 1/4"	7x4x4
351-10000-15-8	10000	15	8	W24X84	9"	360	4416.0	7573	204450.0	10'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-9	10000	15	9	W24X84	9"	360	4541.0	7573	204450.0	11'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-15-10	10000	15	10	W24X84	9"	360	4666.0	7573	204450.0	12'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-11	10000	15	11	W24X84	9"	360	4796.0	7573	204450.0	13'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-12	10000	15	12	W24X84	9"	360	4921.0	7573	204450.0	14'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-13	10000	15	13	W24X84	9"	360	5041.0	7573	204450.0	15'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-14	10000	15	14	W24X84	9"	360	5166.0	7573	204450.0	16'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-15	10000	15	15	W24X84	9"	360	5296.0	7573	204450.0	17'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-16	10000	15	16	W24X84	9"	360	5421.0	7573	204450.0	18'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-17	10000	15	17	W24X84	9"	360	5546.0	7573	204450.0	19'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-18	10000	15	18	W24X84	9"	360	5671.0	7573	204450.0	20'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-19	10000	15	19	W24X84	9"	360	5796.0	7573	204450.0	21'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-15-20	10000	15	20	W24X84	9"	360	5921.0	7573	204450.0	22'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-8	10000	16	8	W24X84	9"	360	4500.0	8102	218752.0	10'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-9	10000	16	9	W24X84	9"	360	4625.0	8102	218752.0	11'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-10	10000	16	10	W24X84	9"	360	4750.0	8102	218752.0	12'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-11	10000	16	11	W24X84	9"	360	4880.0	8102	218752.0	13'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-12	10000	16	12	W24X84	9"	360	5005.0	8102	218752.0	14'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-13	10000	16	13	W24X84	9"	360	5125.0	8102	218752.0	15'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-14	10000	16	14	W24X84	9"	360	5250.0	8102	218752.0	16'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-15	10000	16	15	W24X84	9"	360	5380.0	8102	218752.0	17'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-16	10000	16	16	W24X84	9"	360	5505.0	8102	218752.0	18'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-17	10000	16	17	W24X84	9"	360	5630.0	8102	218752.0	19'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-18	10000	16	18	W24X84	9"	360	5755.0	8102	218752.0	20'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-16-19	10000	16	19	W24X84	9"	360	5880.0	8102	218752.0	21'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-16-20	10000	16	20	W24X84	9"	360	6005.0	8102	218752.0	22'-0"	24"	29"	54"	60"	12	10' X 10' X 4'	6'-6 1/4"	7x4x4
351-10000-17-8	10000	17	8	W24X104	12-3/4"	360	6964.0	7153	236028.0	10'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-9	10000	17	9	W24X104	12-3/4"	360	7123.0	7153	236028.0	11'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-10	10000	17	10	W24X104	12-3/4"	360	7282.0	7153	236028.0	12'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-11	10000	17	11	W24X104	12-3/4"	360	7438.0	7153	236028.0	13'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-12	10000	17	12	W24X104	12-3/4"	360	7597.0	7153	236028.0	14'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-13	10000	17	13	W24X104	12-3/4"	360	7753.0	7153	236028.0	15'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-14	10000	17	14	W24X104	12-3/4"	360	7912.0	7153	236028.0	16'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-15	10000	17	15	W24X104	12-3/4"	360	8068.0	7153	236028.0	17'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-16	10000	17	16	W24X104	12-3/4"	360	8227.0	7153	236028.0	18'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-17	10000	17	17	W24X104	12-3/4"	360	8383.0	7153	236028.0	19'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-18	10000	17	18	W24X104	12-3/4"	360	8542.0	7153	236028.0	20'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-19	10000	17	19	W24X104	12-3/4"	360	8698.0	7153	236028.0	21'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-17-20	10000	17	20	W24X104	12-3/4"	360	8857.0	7153	236028.0	22'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-8	10000	18	8	W24X104	12-3/4"	360	7068.0	7602	250848.0	10'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-9	10000	18	9	W24X104	12-3/4"	360	7227.0	7602	250848.0	11'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-10	10000	18	10	W24X104	12-3/4"	360	7385.8198	7602	250848.0	12'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-11	10000	18	11	W24X104	12-3/4"	360	7542.0	7602	250848.0	13'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-12	10000	18	12	W24X104	12-3/4"	360	7700.8798	7602	250848.0	14'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-13	10000	18	13	W24X104	12-3/4"	360	7857.0	7602	250848.0	15'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-14	10000	18	14	W24X104	12-3/4"	360	8015.9398	7602	250848.0	16'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-18-15	10000	18	15	W24X104	12-3/4"	360	8172.0	7602	250848.0	17'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-16	10000	18	16	W24X104	12-3/4"	360	8330.9998	7602	250848.0	18'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-17	10000	18	17	W24X104	12-3/4"	360	8487.0	7602	250848.0	19'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-18	10000	18	18	W24X104	12-3/4"	360	8646.0598	7602	250848.0	20'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-19	10000	18	19	W24X104	12-3/4"	360	8802.0	7602	250848.0	21'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-18-20	10000	18	20	W24X104	12-3/4"	360	8961.1198	7602	250848.0	22'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-8	10000	19	8	W24X104	12-3/4"	360	7171.0	8054	265772.0	10'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-9	10000	19	9	W24X104	12-3/4"	360	7330.0	8054	265772.0	11'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-10	10000	19	10	W24X104	12-3/4"	360	7490.0	8054	265772.0	12'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-11	10000	19	11	W24X104	12-3/4"	360	7645.0	8054	265772.0	13'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-12	10000	19	12	W24X104	12-3/4"	360	7805.0	8054	265772.0	14'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-13	10000	19	13	W24X104	12-3/4"	360	7961.0	8054	265772.0	15'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-14	10000	19	14	W24X104	12-3/4"	360	8120.0	8054	265772.0	16'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-15	10000	19	15	W24X104	12-3/4"	360	8275.0	8054	265772.0	17'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-16	10000	19	16	W24X104	12-3/4"	360	8435.0	8054	265772.0	18'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-17	10000	19	17	W24X104	12-3/4"	360	8591.0	8054	265772.0	19'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-18	10000	19	18	W24X104	12-3/4"	360	8750.0	8054	265772.0	20'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-19	10000	19	19	W24X104	12-3/4"	360	8907.0	8054	265772.0	21'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-19-20	10000	19	20	W24X104	12-3/4"	360	9065.0	8054	265772.0	22'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-8	10000	20	8	W24X104	12-3/4"	360	7275.0	8510	280800.0	10'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-9	10000	20	9	W24X104	12-3/4"	360	7434.0	8510	280800.0	11'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-10	10000	20	10	W24X104	12-3/4"	360	7593.8198	8510	280800.0	12'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4

Item Id	Capacity (Lbs.)	Span (Ft.)	Height Under Boom (Ft.)	Beam Size	Flange Width	Rotation	Approx. Weight	Anchor Pull Force (Lbs./Bolt)	Overturning Moment (Ft. Lbs.)	Overall Height	Mast Diameter (Inches)	Rotation Clearance	Bolt Circle Diam.	Base Plate Diam.	# Bolts	Foundation	Head Dimension	2Nd Skid Dimensions (Feet)
351-10000-20-11	10000	20	11	W24X104	12-3/4"	360	7749.0	8510	280800.0	13'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-12	10000	20	12	W24X104	12-3/4"	360	7908.8798	8510	280800.0	14'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-13	10000	20	13	W24X104	12-3/4"	360	8065.0	8510	280800.0	15'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-14	10000	20	14	W24X104	12-3/4"	360	8223.9398	8510	280800.0	16'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-15	10000	20	15	W24X104	12-3/4"	360	8379.0	8510	280800.0	17'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-16	10000	20	16	W24X104	12-3/4"	360	8538.9998	8510	280800.0	18'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-17	10000	20	17	W24X104	12-3/4"	360	8695.0	8510	280800.0	19'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-18	10000	20	18	W24X104	12-3/4"	360	8854.0598	8510	280800.0	20'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-19	10000	20	19	W24X104	12-3/4"	360	9011.0	8510	280800.0	21'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4
351-10000-20-20	10000	20	20	W24X104	12-3/4"	360	9169.1198	8510	280800.0	22'-1/2"	30"	38"	66"	72"	12	10' X 10' X 5'	8'-0 1/4"	8.5x5x4